Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No.

25

## NM-2379

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to d Use "APPLICATION FO	drill or to deepen or reentry to a different reservoid DR PERMIT—" for such proposals	6. If indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
Type of Weil     Oil    Gas     Weil    Other      Name of Operator	CONFIDENTIAL	8. Well Name and No.
Pogo Producing Company  3. Address and Telephone No.		Covington A Federal No.  9. API Well No.
P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		30-025-32851 10. Field and Pool, or Exploratory Area  Deal (Torollo Deal arrange Month)
660' FNL & 330' FEL, Section 35, T22S, R32E		Red Tank Delaware West 11. County or Parish. State Lea County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment Recompletion	Change of Plans  New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off Conversion to Injection
	X Other TD & Production Cas	Ing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Drilled 7-7/8" hole to 10,028'. TD reached @ 1000 hrs CST 02/28/95. Logged well w/ Schlumberger. Ran 232 jts 5-1/2", 17#, J-55 & N-80 LT&C casing. Float shoe @ 10,028'. Float collar @ 9984'. Stage tool @ 6596'. Howco cemented 1st stage w/ 820 sx Class "H" + 5 pps Microbond + 2.4 pps KCl + .6% H-322 @ 15.6 ppg. Displace cement and land plug. Drop bomb and open DV tool. Circulated 5 hrs between stages. Recovered 177 sxs excess cement. Cement 2nd stage w/ 818 sxs Class "C" + 12 pps Gilsonite + 2.8 pps KCl + .3% Halad 332 + .3% Halad 344 @ 14.1 ppg. Plug down @ 1615 hrs CST 3/3/95. TOC @ 3800'. ND BOP's and make cut-off. Weld on wellhead & test to 2500 psi.		
1 hereby certify that the foregoing is one and defree	Tide Senior Operations Engineer	
Signed Round Date April 27, 1995  (This space for Federal or State Office use)		
Approved by	Title	Date