

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33012
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG									
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐					7. Lease Name or Unit Agreement Name V. M. HENDERSON				
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RES. ☐ OTHER ☐									
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.					8. Well No. 14				
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240					9. Pool Name or Wildcat TUBB & S, DRINKARD ; PADDOCK				
4. Well Location Unit Letter <u>D</u> ; <u>660</u> Feet From The <u>NORTH</u> Line and <u>990</u> Feet From The <u>WEST</u> Line Section <u>30</u> Township <u>21-S</u> Range <u>37-E</u> NMPM <u>LEA</u> COUNTY									
10. Date Spudded 7/13/95		11. Date T.D. Reached 7/24/95		12. Date Compl. (Ready to Prod.) 8/5/95		13. Elevations (DF & RKB, RT, GR, etc.) 3498' GL, 3513' KB		14. Elev. Csghead	
15. Total Depth 6800'		16. Plug Back T.D. 5265'		17. If Mult. Compl. How Many Zones?		18. Intervals Drilled By		Rotary Tools 0'-6800'	
19. Producing Interval(s), of this completion - Top, Bottom, Name 5408-5510								20. Was Directional Survey Made YES	
21. Type Electric and Other Logs Run GR-DLL-MSFL, GR-LDT-CNL, GR-CBL, GR-CBL								22. Was Well Cored NO	
23. CASING RECORD (Report all Strings set in well)									
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENT RECORD	
8 5/8		24#		1136'		11		500 SACKS	
5 1/2		17#		4005'		7 7/8		2350 SACKS	
24. LINER RECORD									
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN	
NONE									
25. TUBING RECORD									
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN	
2-7/8"									
26. Perforation record (interval, size, and number) 5408-5510, 2 JSPF, 62 HOLES 5134-5143, 2 JSPF, 18 HOLES									
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.									
DEPTH INTERVAL					AMOUNT AND KIND MATERIAL USED				
5408-5510					A/2000G 15%, 120 BSF/1200G 15%, 18000G				
					35#LG, 12000G HCL, 18000G 35#LG				
5134-5143					A/4500G 15%, 57 BS				
28. PRODUCTION									
Date First Production 8/11/95		Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING						Well Status (Prod. or Shut-in) PROD	
Date of Test 9/5/95		Hours tested 24		Choke Size		Prod'n For Test Period		Oil - Bbl. 28	
								Gas - MCF 66	
								Water - Bbl. 122	
								Gas - Oil Ratio 2357	
Flow Tubing Press.		Casing Pressure		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF	
								Water - Bbl.	
								Oil Gravity - API -(Corr.) 35.7	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD								Test Witnessed By M. D. ELMORE	
30. List Attachments DEVIATION									
31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.									
SIGNATURE <u>M. Angie Davila</u>					TITLE <u>Clerk</u>				
TYPE OR PRINT NAME <u>M. Angie Davila</u>					DATE <u>10/9/95</u>				
					Telephone No. <u>397-0443</u>				

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1210'	T. Canyon
T. Salt	2450'	T. Strawn
B. Salt		T. Atoka
T. Yates		T. Miss
T. 7 Rivers		T. Devonian
T. Queen	3470'	T. Silurian
T. Grayburg		T. Montoya
T. San Andres		T. Simpson
T. Glorieta		T. McKee
T. Paddock	5134'	T. Ellenburger
T. Blinebry	5600'	T. Gr. Wash
T. Tubb	6185'	T. Delaware Sand
T. Drinkard	6390'	T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 5408' to 5510'

No. 2, from 5134' to 5143'

No. 3, from to

No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	1210'	1210'	ANHYDRITE				
1210'	2450'	1240'	SALT				
2450'	3470'	1020'	SANDSTONE, DOLOMITE				
3470'	5134'	1664'	DOLOMITE				
5134'	5600'	466'	DOLOMITE				
5600'	6185'	585'	SANDSTONE, DOLOMITE				
6185'	6390'	205'	DOLOMITE				

