

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33015
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil / Gas Lease	

**WELL COMPLETION OR RECOMPLETION REPORT AND LOG**

1a. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER				7. Lease Name or Unit Agreement Name E. H. B. PHILLIPS "B"	
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORKOVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF RES. <input type="checkbox"/> OTHER					
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.				8. Well No. 3	
3. Address of Operator P.O. BOX 730, HOBBS, NM 88240				9. Pool Name or Wildcat MONUMENT TUBB	
4. Well Location Unit Letter <u>C</u> : <u>660</u> Feet From The <u>NORTH</u> Line and <u>1980</u> Feet From The <u>WEST</u> Line Section <u>10</u> Township <u>20-S</u> Range <u>37-E</u> NMPM <u>LEA</u> COUNTY					
10. Date Spudded 7/30/95	11. Date T.D. Reached 8/8/95	12. Date Compl. (Ready to Prod.) 8/10/95	13. Elevations (DF & RKB, RT, GR, etc.) 3554' GR, 3567.8 KB	14. Elev. Csghead 3554'	
15. Total Depth 7100'	16. Plug Back T.D. 6795'	17. If Mult. Compl. How Many Zones?	18. Intervals Drilled By	Rotary Tools 0'-7100'	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 6420-6484					20. Was Directional Survey Made YES
21. Type Electric and Other Logs Run GR-DLL-MSFL;GR-LDT-CNL;GR-CNL					22. Was Well Cored NO

**CASING RECORD (Report all Strings set in well)**

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8 5/8	24#	1150'	11	450 SACKS	
5 1/2	17#	7100'	7 7/8	1545 SACKS	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
NONE					2-7/8"	6315'	

26. Perforation record (interval, size, and number) 6420-6484	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	6420-6484	A/5000G 15%, F/45000G 16/30 SD

28. PRODUCTION							
Date First Production 9/1/95	Production Method (Flowing, gas lift, pumping - size and type pump) PUMPING (2-1/2"X1-1/4"X20')					Well Status (Prod. or Shut-in) PROD.	
Date of Test 10/10/95	Hours tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl. 5	Gas - MCF 96	Water - Bbl. 4	Gas - Oil Ratio 19200
Flow Tubing Press.	Casing Pressure	Calculated 24- Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API -(Corr.) 35.9	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) SOLD	Test Witnessed By M. D. ELMORE
--	-----------------------------------

30. List Attachments DEVIATION SURVEY
--

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.			
SIGNATURE	<u>M. Angie Davila</u>	TITLE	Clerk
TYPE OR PRINT NAME		M. Angie Davila	DATE
			12/11/95
		Telephone No.	397-0443

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

### Southeastern New Mexico

T. Anhy	1304'	T. Canyon
T. Salt		T. Strawn
B. Salt		T. Atoka
T. Yates		T. Miss
T. 7 Rivers		T. Devonian
T. Queen	3570'	T. Silurian
T. Grayburg	3745'	T. Montoya
T. San Andres		T. Simpson
T. Glorieta		T. McKee
T. Paddock	5290'	T. Ellenburger
T. Blinberry	5630'	T. Gr. Wash
T. Tubb	6390'	T. Delaware Sand
T. Drinkard	6700'	T. Bone Springs
T. Abo	7100' TD	T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (Bough C)		T.

### Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzte
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

## OIL OR GAS SANDS OR ZONES

No. 1, from 6420' to 6484'

No. 2, from to

No. 3, from to

No. 4, from to

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from to feet

No. 2, from to feet

No. 3, from to feet

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	1304'	1304'	ANHYDRITE				
1304'	3570'	2266'	SANDSTONE, DOLOMITE				
3570'	3745'	175'	DOLOMITE				
3745'	5290'	1545'	DOLOMITE				
5290'	5630'	340'	DOLOMITE				
5630'	6390'	760'	SANDSTONE, DOLOMITE				
6390'	6700'	310'	DOLOMITE				
6700'	7100'	400'	DOLOMITE				