

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33277
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	B 1534

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. Lease Name or Unit Agreement Name STATE J-2 (003107)
2. Name of Operator CONOCO INC. <005073>	8. Well No. 17
3. Address of Operator 10 Desta Drive Ste 100 W, Midland, TX 79705	9. Pool name or Wildcat Eumont Yates 7 Rvrs Qn Gas
4. Well Location Unit Letter I : 1340 Feet From The SOUTH Line and 990 Feet From The EAST Line Section 2 Township 22 S Range 36 E NMPM LEA County	10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☒
OTHER: ☒	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: SET SURFACE & PROD. CSG ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-24-96 MIRU. SPUD 12 1/4" HOLE, DRILL TO A DEPTH OF 450'. GIH W/ 18 JTS 8 5/8" 24# K-55 ST&C CSG SET @ 450'. SHOE SET @ 450'. COLLAR SET @ 405'. LEAD SLURRY 250 SX CLASS 'C' + 4% GEL + 2% CACL2. TAIL SLURRY 100 SX CLASS 'C' + 2% CACL2. DISPLACED W/ 25 bbl FRESH WATER. CEMENT RETURNS OF 65 bbl. BUMPED PLUG @ 5:30 am OF 2-25-96 W/ 500 PSI. NMOCD WAS NOTIFIED @ 7 pm ON 2-24-96.

2-26-96 CONTINUED DRILLING 7 7/8" HOLE TO TD @ 3660'. GIH W/ 85 JTS 4 1/2" 11.6# J-55 LT&C CSG SET @ 3660'. SHOE SET @ 3660'. COLLAR SET @ 3615'. LEAD SLURRY 560 SX 35/65/6 POZ + 5# SALT + 0.2% SM. TAIL SLURRY 400 SX CLASS 'C' + 1.1% FLO BLOCK 210 + 0.2% SM. CEMENT RETURNS OF 150 bbl. BUMPED PLUG @ 2:50 am ON 3-3-96 W/ 1800 PSI. NMOCD WAS NOTIFIED @ 6 pm ON 3-2-96.

3-3-96 RDMO.

CURRENTLY WAITING ON COMPLETION RIG.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE <i>Bill R. Keathly</i>	TITLE SR. REGULATORY SPEC.	DATE 3-6-96
TYPE OR PRINT NAME BILL R. KEATHLY		TELEPHONE NO. 915-686-5424

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 13 1996

