

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-33357
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil / Gas Lease	
7. Lease Name or Unit Agreement Name	NEW MEXICO "H" STATE NCT-1
8. Well No.	25
9. Pool Name or Wildcat	EUMONT YATES SEVEN RIVERS QUEEN (PRO GAS)

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER _____	7. Lease Name or Unit Agreement Name NEW MEXICO "H" STATE NCT-1			
b. Type of Completion: NEW WELL ☒ WORKOVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RES. ☐ OTHER _____				
2. Name of Operator TEXACO EXPLORATION & PRODUCTION INC.	8. Well No. 25			
3. Address of Operator 205 E. Bender, HOBBS, NM 88240	9. Pool Name or Wildcat EUMONT YATES SEVEN RIVERS QUEEN (PRO GAS)			
4. Well Location Unit Letter <u>O</u> : <u>660</u> Feet From The <u>SOUTH</u> Line and <u>1650</u> Feet From The <u>EAST</u> Line Section <u>31</u> Township <u>20S</u> Range <u>37E</u> NMPM <u>LEA</u> COUNTY				
10. Date Spudded 4/3/96	11. Date T.D. Reached 4/8/96	12. Date Compl. (Ready to Prod.) 5/3/96	13. Elevations (DF & RKB, RT, GR, etc.) 3542 GL	14. Elev. Csghead
15. Total Depth 3600'	16. Plug Back T.D. 3564'	17. If Mult. Compl. How Many Zones?	18. Intervals Drilled By PRIDE	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name 3188'-3518' EUMONT				20. Was Directional Survey Made YES
21. Type Electric and Other Logs Run Cased Hole				22. Was Well Cored no

CASING RECORD (Report all Strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENT RECORD	AMOUNT PULLED
8-5/8"	24#	455'	11"	200 SX, CIRC	
5-1/2"	15.5#	3600'	7-7/8"	1100 SX, CIRC	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-3/8"	3472'	

26. Perforation record (interval, size, and number) 3188'-3518'	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 3188'-3518' 3188'-3518' 12/20 sand, 40000# 12/20 resin	AMOUNT AND KIND MATERIAL USED acid w/4500 gals 15% NEFE frac w/80000 gals 50Q CO2, 274000#
--	---	--

28. PRODUCTION							
Date First Production 5/3/96	Production Method (Flowing, gas lift, pumping - size and type pump) pumping (2" X 1-1/4" X 16')					Well Status (Prod. or Shut-in) Producing	
Date of Test 7-96	Hours tested 24	Choke Size open	Prod'n For Test Period	Oil - Bbl. 0	Gas - MCF 376	Water - Bbl. 6	Gas - Oil Ratio
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API -(Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold	Test Witnessed By TVS
--	--------------------------

30. List Attachment Deviation Survey

31. I hereby certify that the information on both sides of this form is true and complete to the best of my knowledge and belief.			
SIGNATURE <i>Paula S. Ives</i>	TITLE Engineering Assistant	DATE 8/22/96	Telephone No. 397-0432
TYPE OR PRINT NAME Paula S. Ives			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall be reported. For multiple completions, items 20 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anny	1078'	T. Canyon
T. Salt	1206'	T. Strawn
B. Salt	2504'	T. Atoka
T. Yates	2638'	T. Miss
T. 7 Rivers	2910'	T. Devonian
T. Queen	3334'	T. Silurian
T. Grayburg		T. Montoya
T. San Andres		T. Simpson
T. Glorieta		T. McKee
T. Paddock		T. Ellenburger
T. Blinberry		T. Gr. Wash
T. Tubb		T. Delaware Sand
T. Drinkwater		T. Bone Springs
T. Abo		T.
T. Wolfcamp		T.
T. Penn		T.
T. Cisco (rough C)		T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn "B"
T. Kirtland-Fruitland	T. Penn "C"
T. Pictured Cliffs	T. Penn "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzite
T. Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from	3188'	to	3518'	No. 3, from		to	
No. 2, from		to		No. 4, from		to	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole

No. 1, from		to		feet	
No. 2, from		to		feet	
No. 3, from		to		feet	

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	1078	1078	ANHYDRITE				
1078	1206	128	SALT				
1206	2504	1298	SALT				
2504	2638	134	SAND, DOLOMITE				
2638	2910	272	DOLOMITE				
2910	3334	424	DOLOMITE				