

OPER. CGRID NO. 17891PROPERTY NO. 9325

TUN

FORM APPROVED
OMB NO. 1004-0136
Expires: February 28, 1995UNITED
DEPARTMENT OF
BUREAU OF LANDPOOL CODE 51683EXP. DATE 10/29/96APR. NO. 30-025-33651

240

APPLICATION FOR PERM.

1A. TYPE OF WORK

DRILL ☒DEEPEN ☐

B. TYPE OF WELL

OIL
WELL ☒GAS
WELL ☐OTHER ☐SINGLE
ZONE ☒MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

POGO PRODUCING COMPANY

(RICHARD WRIGHT)

3. ADDRESS AND TELEPHONE NO.

P.O. BOX 10340 MIDLAND, TEXAS 79702

Ph. 915-682-6822

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
At surface990' FNL & 1980' FWL SEC. 27 T22S-R32E LEA CO. NEW MEXICO
At proposed prod. zone Same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

Approximately 30 miles East of Carlsbad, New Mexico

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

990'

16. NO. OF ACRES IN LEASE

320

17. NO. OF ACRES ASSIGNED
TO THIS WELL

40

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

990'

19. PROPOSED DEPTH

9000'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

3633' GR.

22. APPROX. DATE WORK WILL START*

As soon as approved

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE, SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
26"	20" Conductor	NA	40'	Cement to surface W/Redi-Mix
14 3/4"	H-40 10 3/4"	32.75	800'	650 Sx. circulate cement to surface
9 7/8"	J-55, N-80 7 5/8"	26.4	4650'	1300 Sx. circulate cement to surface
6 3/4"	J-55, N-80 4 1/2"	11.6	9000'	1100 Sx. Top of cement 3600'

1. Drill 26" hole to 40'. Set 40' of 20" conductor cement to surface W/Redi-Mix.
2. Drill 14 3/4" hole to 800'. Run and set 800' of H-40 32.75# ST&C casing. Cement with 650 Sx. Class "C" cement + additives, circulate cement to surface.
3. Drill 9 7/8" hole to 4650'. Run and set 4650' of 7 5/8" 26.4# casing, 1500' of N-80, 3000' of J-55 and 150' of N-80. Cement with 800 Sx. Halco Light tail in with 500 Sx. Premium + additives, circulate cement to surface.
4. Drill 6 3/4" hole to 9000'. Run and set 9000' of 4 1/2" 11.6 # casing, 1500' of N-80 LT&C, 4800' of J-55 LT&C, 2700' of N-80 LT&C casing. Cement with 700 Sx. Halco Light + additives, tail in with 400 Sx. Premium Plus + additives, bring cement back to 3600' verify with log.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

TITLE Agent

DATE

09/14/96

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject tract which would entitle the applicant to conduct operations thereon.

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

(ORIG. SGN.) RICHARD L. MANUS

Area Manager

DATE

OCT 23 1996

*See Instructions On Reverse Side