

ATTACHMENT TO FORM C-105
COLLINS & WARE, INC.
M & M #3

26. Perforation Record.

6898' - 7002'	44 holes	7/07/97	Drinkard
6673' - 6829'	1 SPF	7/18/97	Lower Tubb
6546' - 6579'	1 SPF	7/21/97	Lower Tubb
5951' - 6099'	1 SPF (41 perfs)	7/25/97	Blinebry

27. Treatment Record.

6898' - 7002'	AT with 2000 gals 15% Ferchek acid with 668 ball sealers. Had fair ball action. 7/7/97
6898' - 7002'	FT with 30,000 gals Delta-Frac 25 carrying 1000 sx 20/40 Ottawa sand. 7/8/97
6819' - 6829'	AT with 200 gals 15% NEFE acid. 7/19/97
6762' - 6772'	AT with 450 gals 15% NEFE acid. 7/19/97
6673' - 6829'	AT with 2250 gals 15% NEFE acid with 60 ball sealers. 7/19/97
6546' - 6579'	AT with 1500 gals 15% NEFE acid and 25 BS. 7/22/97
6883'	Set CIBP at 6883' and dump 4 sx cement on top of plug. 7/25/97
6510'	Set CIBP at 6510' and dump 4 sx cement on top of plug. 7/25/97
5951' - 6099'	AT with 2500 gals 15% Ferchek SC acid. 7/27/97
5951' - 6099'	FT with 50,000 gals Delta-Frac 25 carrying 140,000# 20/40 Ottawa sand. 7/97