Submit 3 Copies to Appropriate District Office

1. Type of Well: MET X

2. Name of Operator

3. Address of Operator

PERFORM REMEDIAL WORK

TEMPORARILY ABANDON

PULL OR ALTER CASING

4. Well Location

11

OTHER:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

x

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM \$8210

DISTRICT III
1000 Rio Brazos Rd., Aziec, NM 87410

CASING TEST AND CEMENT JOB

Set Surface Casing

istrict Cities		N. DIVICION	<u> </u>		
ISTRICT 1 O. Box 1980, Hobbs, NM 88240	OIL CONSERVATION DIVISION		WELL API NO.	107	
O. Box 1980, Hobbs, NM 88240 310 Old Santa Fe Trail, Room 206 SISTRICT II Santa Fe, New Mexico 87503			30-025-33927		
ISTRICT II O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mex	5. Indicate Type of Lease STATE FEE X			
ISTRICT III 000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease N/A	No.	
CUMPRYMOT	TOTE AND REPORTS ON WE	IS			
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name Kyte		
Type of Well:					
OE GAS WELL X	OTHER				
Name of Operator			8. Well No.		
Stevens & Tull	. Inc.		5		
Address of Operator			9. Pool name or Wildcat		
•	, Midland, TX 79702		DK Abo		
Well Location	,				
	80 Feet From The North	Line and198	80 Feet From The _	East Line	
Section 23	Township 20S R	ange 38E	NMPM Lea	County	
	10. Elevation (Show whether				
Check	Appropriate Box to Indicate	Nature of Notice, F	Report, or Other Data	•	
NOTICE OF IN		SUE	BSEQUENT REPO	RT OF:	
RFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTER	RING CASING	
MPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLIN	GOPNS. PLUG	AND ABANDONMENT	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

OTHER:_

4/24/97 - Spud 12 1/4" hole at 3:00 p.m. MST

4/25/97 - TD 12 1/4" hole at 1631'. Run 39 joints 8 5/8" - 24# - J55 casing to 1631!. Cement with 550 sx "c" plus 6% gel plus tail with 200 sx "c" plus 2% CaCl, - circulate 80 sx to pit

APPROVED BY - CONDITIONS OF	APPROVAL, IF ANY	:			
(This space for S	ute Use)	1、1000年(1900年),1000年代 1、1000年(1900年)。1000年代 20 0年(1900年)	mue	date	- 1941 F. B. 1997.
TYPE OR PRINT!	(AME		TELETINE NO.		
-		above is true and complete to the best of my knowledge	e and belief.	DATE	4/29/97
,	4/27/97 -	Start drilling 7 7/8" ho Tested BOP to 2000 psi	ole - install H ₂ S safety equipme	ent	
		WOC - 18 hours before dr	rilling out.		