

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. BOX 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33946

5. Indicate Type of Lease

☐ STATE

☒ FEE

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Deck Estate

8. Well No.

1

9. Pool name or Wildcat

Hardy Simpson Ellenburger

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

☒ OIL WELL

☐ GAS WELL

☐ OTHER

2. Name of Operator

APACHE CORPORATION

m w Petroleum Corp

3. Address of Operator

2000 POST OAK BLVD., SUITE 100, HOUSTON, TX 77056-4400

4. Well Location

Unit Letter I : 1980'

Feet From The South

Line and 330'

Feet From The East

Line

Section 35

Township

20S

Range

37E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3492' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

☐ Perform Remedial Work

☐ Plug and Abandon

☐ Remedial Work

☐ Altering Casing

☐ Temporarily Abandon

☐ Change Plans

☐ Commence Drilling Operations

☐ Plug and Abandonment

☐ Pull or Alter Casing

☒ Casing Test and Cement Job

☐ Other

☐ Other - Spud

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)
SEE RULE 1103.

6/9/97 Rig up Halliburton & spot 60 sx plug @ 10,100'-9900'. TOOH w/ 21 stds. Spot 75 sx plug @ 8100'-7900'. TIH w/ bit to bottom of 8-5/8" csg. WOC.

6/10/97 TIH to dress cement. WOC. Wash to top of plug, found that plug had moved down hole. Top of plug @ 8010'. Lay down drill pipe & drill collars. Drld. 7-7/8" hole to 7900'. Run 178 jts. 5-1/2", 17#, K-55 LT&C. Cmt'd w/ 1200 sks. Top of Float collar @ 7805'. Top of Float shoe @ 7898'. Finish cementing & rig down Halliburton. ND & p/u BOP. NU & test tubing hanger. Rig released @ 2:00 p.m.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Deborah K. Hoyt

TITLE

Engineering Tech.

DATE

6/17/97

TYPE OR PRINT NAME

Deborah K. Hoyt

TELEPHONE NO. 713-296-7152

(This space for State Use)

ORIGINAL SIGNED BY CHIEF OF DIVISION
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: