

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33989

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil / Gas Lease No.

7. Lease Name or Unit Agreement Name

E. H. B. PHILLIPS C

8. Well No.

2

9. Pool Name or Wildcat

ABO

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMITS
(FORM C-101) FOR SUCH PROPOSALS.

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator

TEXACO EXPLORATION & PRODUCTION INC.

3. Address of Operator

P.O. Box 2100, Denver Colorado 80201

4. Well Location

Unit Letter H : 1980 Feet From The NORTH Line and 660 Feet From The EAST Line
Section 10 Township 20-S Range 37-E NMPM LEA COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

GR-3556', KB-3569'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPERATION ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

PRODUCTION CSG. ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. DRILLED 7 7/8 INCH HOLE TO 7400'. TD @ 4:15 AM 03-17-98.

2. SCHLUMBERGER LOG PLATFORM EXPRESS: PULL 7400' TO 2400', GR - CNL 7400' - 0'.

3. RAN 168 JOINTS OF 5 1/2 INCH, 15.5# 50 AND LS65, LTC CASING SET @ 7400.

4. DOWELL CEMENTED: 1ST STAGE - 500 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.33 CF/S).
CIRCULATED 50 SACKS. 2ND STAGE - 1213 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.4 PPG, 2.10 CF/S).
F/B 102 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.33 CF/S). PLUG DOWN @ 4:30 PM 03-20-98.
NO CEMENT TO SURFACE.

5. ND. RELEASE RIG @ 10:30 PM 03-20-98.

6. PREP TO COMPLETE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE C.P. Basham / S.R.D. TITLE Eng. Assistant.

DATE 3/23/98

TYPE OR PRINT NAME Sheilla D. Reed-High

Telephone No. (303)793-4851

(This space for State Use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE