



## PROPOSED MUD PROGRAM

### CASING DESIGN

8 5/8" Surface Casing at 1,600'  
7 7/8" Open Hole to 8,000'

### RECOMMENDED MUD PROPERTIES

<u>DEPTH</u>	<u>MUD WEIGHT</u>	<u>VISCOSITY</u>	<u>FLUID LOSS</u>
Spud	8.4- 8.6	32-34	No Control
500'	8.6- 8.8	32-34	No Control
1,000'	8.8- 9.2	32-34	No Control
1,300'	9.0- 9.4	32-34	No Control
1,600'	9.0- 9.4	32-34	No Control
Set 8 5/8" Surface Casing at 1,600'. Drill out with Brine Water.			
2,000'	9.6-10.0	28-29	No Control
3,000'	10.0-10.1	28-29	No Control
4,000'	10.0-10.1	28-29	No Control
5,000'	10.0-10.1	28-29	No Control
6,000'	10.0-10.1	28-29	No Control
6,900'	10.1-10.2	30-32	<10
7,400'	10.1-10.2	30-32	<10
7,700'	10.1-10.2	30-32	<10
8,000'	10.1-10.3	32-34	<10

### RECOMMENDED MUD PROGRAM BY CASING INTERVAL

#### Surface Hole 0-1,650'

Spud with a Gel/Lime slurry, mixing one Lime per ten Gel for a 32-34 viscosity. Once the shallow poorly-consolidated surface formations have been drilled, allow the native solids to maintain a viscosity of 32-34 sec./qt. It is important that a stable viscosity be maintained with constant additions of fresh water at the flowline.

Hole conditions will dictate the need for any additional viscosity at total depth to insure good conditions for casing operations.