

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	34672 30-025-34692
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	State 'A' A/C 2
8. Well No.	76
9. Pool name or Wildcat	Eunice: Seven Rivers-Queen, South (24130)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> OTHER	2. Name of Operator Raptor Resources, Inc.
3. Address of Operator 901 Rio Grande, Austin, TX 78701	4. Well Location Unit Letter <u>E</u> <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>8</u> Township <u>22S</u> Range <u>36E</u> NMPM <u>Lea</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3601'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER <input checked="" type="checkbox"/>	Spud & set Surface Casing

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-9-00 Supd 12 1/4" hole @ 2 pm on 3-9-00. Drill 12 1/4" hole to a depth of 630'. GIH W/ 14 jts 8 5/8" 24# casing set @ 630'. Cement (lead cmt) W/ 140 sx Class 'C' + 2% CaCl + 6% Bentonite gel. Tail cement 100 sx Class 'C' + 2% CaCl, circulate 89 sx to surface. Plug down @ 1:15 am on 3-10-00. WOC.

Continue drilling 7 7/8" hole to total depth.

12. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bill R. Keathly TITLE R regulatory Agent for Raptor DATE 3-14-00

TYPE OR PRINT NAME Bill R. Keathly TELEPHONE NO. 915-697-1609

(this space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: