


VICINITY MAP



SCALE: 1" = 2 MILES

SEC. 31 TWP. 20-S RGE. 37-E

SURVEY N.M.P.M.

COUNTY LEA

DESCRIPTION 2490' FSL & 184' FWL


ELEVATION 3531

CHEVRON U.S.A.
OPERATOR PRODUCTION COMPANY

LEASE EMSU

JOHN WEST SURVEYING
HOBBS, NEW MEXICO
(505) 393-3117

WORTH



SEC. 31 TWP. 20-S RGE. 37-E

SURVEY N.M.P.M.

COUNTY LEA

DESCRIPTION 2490' FSL & 184' FWL

ELEVATION 3531

CHEVRON U.S.A.
OPERATOR PRODUCTION COMPANY

LEASE EMSU

U.S.G.S. TOPOGRAPHIC MAP


MONUMENT SOUTH, N.M.

*JOHN WEST SURVEYING
HOBBS, NEW MEXICO
(505) 393-3117*

CHEVRON DRILLING REFERENCE SERIES
VOLUME ELEVEN
WELL CONTROL AND BLOWOUT PREVENTION

D. CLASS II-B BLOWOUT PREVENTER STACK:

Figure 11J.3
Class II-B Blowout Preventer Stack



The Class II-B preventer stack is designed for drilling or workover operations. It is composed of a single hydraulically operated annular preventer on top, then a drilling spool, and a single blind ram preventer on bottom. In an alternate configuration, a single pipe ram preventer may be substituted for the annular preventer. The choke and kill lines are installed onto the drilling spool and must have a minimum internal diameter of 2". An emergency kill line may be installed on the wellhead. As the maximum anticipated surface pressure of this stack is less than 2000 psi, screwed connections may be used. All components must be of steel construction. The Class II-B blowout preventer stack is shown to the left in Figure 11J.3.