Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division FORM APPROVED
Budget Bureau No. 1004-0135
1625 N. French Dr. Expires: March 31, 1993
Hobbs. NW 38240 Lease Designation and Seriai No.

Do not use this form for proposals to dri	Hobbs, NW 382 AND REPORTS ON WELLS Il or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	LC 031670A 6. If Indian, Allotee or Tribe Name
SUBMIT IN TRIPLICATE 1. Type of Well		7 If Unit or CA, Agreement Designation
Oil Well Well Other		8. Well Name and No.
2. Name of Operator		SEMU Burger, Well #141
CONOCO INC.		9. API Well No.
3 Address and Telephone No. 10 DESTA DR. STE. 100W, MIDLAND, TX. 79705-4500 (915) 686-5580/684-6381		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage. Sec., T. R. M. or Survey Description)		Eumont Yates Seven Rvrs On
1300' FNL & 1150' FWL, Section 19, T20S, R38E		11. County or Parish, State
		Lea County, NM
In CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Repon	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing Other Casing squeeze	Conversion to Injection
		Dispose Water Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
	pertinent details, and sive pertinent dates, including estimated date of startin al depths for all markers and zones pertinent to this work.)*	g any proposed work. If well is directionally drilled
3-15-00: Pumped & spotted 200 gals 15% HCL 3-16-00: Perforated from 2475-2479 w/4 JSPF retainer set @ 2493', mixed & pumped 50 sx C pulled up to 2430', reverse circulated clean, pul 3-17-00: Tagged cement @ 2424',RIH w/bit, d 3-18-00: Drilled on cement @ 2451', soft, teste 3-19-00: RIH w/5 l/2" cement retainerset @ 24 water, pressured upto 1500# & shut in. Calculat 3-22-00: Tagged cement @ 2320', started drilli leaked off 10# in 5 minutes. Pulled up above sq 3-23-00: Drilling out cement @2485', drilled ow/packer set @2495' pressured to 1500# both sc 3-28-00: Spotted 2 sx sand on top of RBP, mix 3-29-00: Fished & latched onto RBP, released, 3-30-00: Ran 2 7/8" tubing to 3040', pickled tul packer @ 2934'. Removed BOP & installed pro	ged down wireline, pressured 5 1/2" to 1000#, bled down from 2509', pulled up hole to 2265', closed BOP, press, RIH w/packer to 2495', circulated through perfs, POO at C cement w/1.2% FL-33, 0.4% CD-32 & 2% CaCl2, colled up to 2250', pressured up casing to 500# & SION. In the single of the singl	ssure tested-POH w/tbg, SION. OH w/packer, RIH w/5 1/2" cement displaced, stung out of retainer, bulled up & circulated. SION. 230'. SION. urry & displaced w/l4 bbls fresh seeze holes @ 2475-2479' to 1500#, 508-2509', circulated well, RIH @ 2655'. SION. cement to 1990#, SION.
14. I hereby certify that the foregoing is true and project.	Ann E. Ritchie	viii.
Signed Mul Ville his	Title Regulatory Agent	Date4-12-00
(This space for Federal or State office use)	URIGITAL SIGNED BY OF THE	
Approved by	Title	Date MAY 7 2 2000
BLM(6), BRK		

* ...

PR 1 7 2000
BLM
ROSWELL, NM

