

DISTRICT I

P.O. Box 1980 Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO
30-025-34970
Indicate Type of Lease
STATE FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well
OIL WELL <input checked="" type="checkbox"/> GAS WELL OTHER

Name of Operator
Trilogy Operating, Inc

Address of Operator
P.O. Box 11005, Midland, Texas 79702

Well Location
Unit Letter J 1980 Feet From The South Line and 1980 Feet From The East Line
Section 1 Township 20S Range 38E NMPM Lea County

Elevation (Show whether DF, RKB, RT, GR, etc.)
3484 GR

Lease Name or Unit Agreement Name
Howser

Well No
1

Pool name or Wildcat
House Drinkard

11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	PLUG AND ABANDON
TEMPORARILY ABANDON	CHANGE PLANS
PULL OR ALTER CASING	
OTHER:	

SUBSEQUENT REPORT OF:

REMEDIAL WORK	ALTERING CASING
COMMENCE DRILLING OPNS	PLUG AND ABANDONMENT
CASING TEST AND CEMENT JOB	
OTHER:	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103

3/14/00 - Spud 12 1/4" hole w/ fresh water mud @ 11:00 PM

3/15/00 - TD surface hole @ 1507' - RIH w/ 36 lbs 8 5/8" - 24# - J55 casing to a setting depth of 1507'
Cement w/ 500 sx "c" + 4% gel + 2% CaCl2 + 200 sx "c" + 2% CaCl2 - circulated 108 sx to surface

3/17/00 - WOC 18 hrs before drilling out w/ 7 7/8" bit w/ brine mud system - BOP was tested to 3000 psi

4/03/00 - TD 7 7/8" hole @ 7900' - run open hole logs - decide to set casing

4/04/00 - RIH w/ 192 lbs of 5 1/2" 15.50 & 17.00# - J55 casing to a setting depth of 7902'
Cement w/ 1456 sx (65:35:6) class "c" + 1/4 #/sx celloflake + 435 sx class "h" + 0.5% FL-25
Circulate 65 sx cement to surface

4/06/00 - RDMO Key Drilling Rig # 40 - Prepare to begin completion attempts

I hereby certify that the information above is true and complete to the best of my knowledge and belief

SIGNATURE  TITLE Consulting Engineer DATE 04-22-00
TYPE OR PRINT NAME Michael G. Mooney TELEPHONE NO 915/699-1410

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: