

Measured Depth	Inclin. Degrees	Azimuth Degrees	True Vert Depth	R E C T A N G U L A R C O O R D I N A T E S	Dogleg Deg/100ft
0.00	0.00	0.00	0.00	0.00 E	0.00
100.00	0.54	263.74	100.00	0.47 W	0.54
200.00	0.47	223.71	199.99	1.22 W	0.35
300.00	0.80	257.71	299.99	2.19 W	0.49
400.00	2.92	224.57	399.93	4.66 W	2.29
500.00	5.30	221.36	499.67	9.50 W	2.39
600.00	5.64	221.64	599.21	15.81 W	0.34
700.00	6.91	211.82	698.61	22.25 W	1.66
800.00	7.55	209.04	797.82	28.61 W	0.73
900.00	7.85	206.19	896.92	34.81 W	0.49
1000.00	8.79	201.50	995.87	59.98 S	1.16
1100.00	9.98	199.61	1094.53	75.25 S	1.23
1200.00	9.69	192.33	1193.06	91.63 S	1.28
1300.00	10.38	189.87	1291.53	108.73 S	0.81
1400.00	12.04	188.62	1389.62	127.92 S	1.68
1500.00	13.65	187.16	1487.11	149.94 S	1.64
1600.00	15.70	185.91	1583.85	175.11 S	2.07
1700.00	17.76	184.41	1679.61	203.78 S	2.10
1800.00	19.52	183.28	1774.36	235.67 S	1.80
1900.00	21.77	182.74	1867.93	270.87 S	2.26
2000.00	23.50	181.71	1960.23	309.33 S	1.77
2100.00	25.46	181.46	2051.23	350.75 S	1.96
2200.00	27.05	181.17	2140.91	394.97 S	1.60

All data is in feet unless otherwise stated.
 Coordinates from slot #1 and TVD from rotary table.
 Bottom hole distance is 401.76 on azimuth 190.55 degrees from wellhead.
 Calculation uses the minimum curvature method.
 Presented by Baker Hughes INTEQ