

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
1625 N. French Dr.
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
House Designation and Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

CONOCO INC.

3. Address and Telephone No.

10 DESTA DR. STE. 100W, MIDLAND, TX. 79705-4500 (915) 686-5580/684-6381

4. Location of Well (Footage, Sec., T. R. M. or Survey Description)

Section 30, T20S, R38E, 1730' FNL & 960' FWL

LC.031695A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

SEMU, Well #149

9. API Well No.

30 025 35169

10. Field and Pool, or Exploratory Area

North Hardy Strawn

11. County or Parish, State

Lea County, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Repon
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Spud, casing strings & TD

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)


13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-12-00: Well spudded - drilling 12 1/4" hole.

12-14-00: Ran 8 5/8", 24#, J-55 casing to 1522'. Cemented with 178 bbls lead cement, 48 bbl tail cement. Displaced w/94 bbls water. Bumped plug w/800 psi. WO Cement. Tested casing 2000#, rams 2000#, annular 1500#, remainder 3000#.

1-6-01: Logged and ran sidewall cores.

1-7-01: Ran 5 1/2" casing to total depth of 7906'. Total depth of well: 7910'. Cemented 5 1/2" with 3 stage cement. Plug down w/2300 psi - tool closed, no cement circulated to surface. Tested to 2500 psi - held okay. Rig released.



14. I hereby certify that the foregoing is true and correct

Signed

Title

Ann E. Ritchie
Regulatory Agent

Date

1-10-01

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval if any:

BLM(6)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

GWV