

DRILLING PROGRAM  
Melrose Operating Co.  
**Closson B Federal # 40**  
660' FNL, 1650' FWL  
Unit C, Sec. 19, T22S, R36E  
Lea Co., NM

1. Geologic Name of Surface Formation:

Quaternary Alluvium

2. Estimated Tops of Important Geologic Markers:

Top of salt	1650'
Base of salt	3340'
Tansill	3360
Yates	3490
7-Rivers	3780

3. Estimated Depth of Anticipated Fresh Water, Oil or Gas:

Water Sand	100' - 150'	Fresh Water
Yates	3490-3780'	Oil & Gas
7-Rivers	3780+	Oil & Gas

Fresh water sands will be protected by running 8-5/8" casing to a minimum depth of 400' and circulating cement. All other zones will be isolated by running "4-1/2" or "5-1/2" production casing and circulating cement.

4. Casing Program:

<u>Hole Size</u>	<u>Interval</u>	<u>OC Csg</u>	<u>Weight Grade Jt Cond Type</u>
12-1/4"	0 - 400	8-5/8"	24#, J55, New
7-7/8"	1500 - TD	4-1/2"	9.5# - 10.5#, J55, Used

Cement Program:

8-5/8" Surface Casing: Cemented to surface with 375 sx of Class C with 2% CaCl and 1/4#/sx Flocele.

4-1/2" Production Casing: Cemented with 300 sx of Class C and 400 sx of Lite C with 6# salt/sx and 1/4#/sx Flocele. This should circulate cement to the surface.

5. Minimum Specifications for Pressure Control:

The blowout preventer equipment (BOP) shown in Exhibit #2 will consist of a double ram type preventer (3000 psi WP). Unit will be hydraulically operated. BOP will be nipped up on the 8-5/8" surface csg and used continuously until TD is reached. BOP and accessory equipment will be tested to 1000 psi before drilling out of surface casing. A 2" kill line and a 2" choke line will be included in the drilling spool. Other accessories to the BOP equipment will include a kelly cock.