

LEASE & WELL BELL LAKE UNIT # 22 Unit P 660/S 4990/E
(Give Unit, Section, Township and Range)

OPERATOR DEVON SFS OPERATING, INC. 30-025-35592

DRILLING CONTRACTOR NABORS DRILLING USA, LP

The Undersigned hereby certifies that he is an authorized representative of the drilling contractor who drilled the above-described well and that he has conducted deviation tests and obtained the following results:

DEGREES @ DEPTH		DEGREES @ DEPTH		DEGREES @ DEPTH		DEGREES @ DEPTH	
1/2	341	1	3498	1	9939		
2	828	1	3998	3/4	10439		
2	939	3/4	4498	3/4	10924		
2 1/4	1142	1 3/4	4821	1	11424		
5 3/4	1355	2	4984	1 1/2	12011		
5 3/4	1449	2	5235	3/4	12386		
5 1/2	1516	1 3/4	5510	1	12643		
4 1/4	1605	1 1/2	6040	1	12822		
4	1698	1 1/2	6573	1 1/4	13236		
3 1/4	1760	1 1/2	7073				
3	1822	1	7572				
2 1/4	1917	1 1/4	7938				
2	2052	1 1/4	8431				
1/2	2533	1	8939				
1 1/2	3000	1	9439				

Drilling Contractor Nabors Drilling USA, LP
By Brent Sanders-Manager Contracts & Marketing

Subscribed and sworn to before me this 16th day of December, 2001

My Commission Expires Donna Westbrook Notary Public State of Texas My Comm Exp. 12-29-2004
County TEXAS



Water Analysis

Date: 13-Oct-01

2708 West County Road, Hobbs NM 88240

Phone (505) 392-5556 Fax (505) 392-7307

Analyzed For

Company	Well Name	County	State
DEVON ENERGY	BELL LAKE #22	Lea	New Mexico

Sample Source	TEST UNIT	Sample #	1
Formation	UNKNOWN	Depth	UNKNOWN

Specific Gravity	1.040	SG @ 60 °F	1.042
pH	6.77	Sulfides	Absent
Temperature (°F)	70	Reducing Agents	

Cations

Sodium (Calc)	in Mg/L	19,123	in PPM	18,352
Calcium	in Mg/L	400	in PPM	384
Magnesium	in Mg/L	168	in PPM	161
Soluble Iron (FE2)	in Mg/L	250.0	in PPM	240

Anions

Chlorides	in Mg/L	30,400	in PPM	29,175
Sulfates	in Mg/L	396	in PPM	380
Bicarbonates	in Mg/L	303	in PPM	290
Total Hardness (as CaCO3)	in Mg/L	1,700	in PPM	1,631
Total Dissolved Solids (Calc)	in Mg/L	51,040	in PPM	48,982
Equivalent NaCl Concentration	in Mg/L	48,483	in PPM	46,528

Scaling Tendencies

*Calcium Carbonate Index 121,024

Below 500,000 Remote / 500,000 - 1,000,000 Possible / Above 1,000,000 Probable

*Calcium Sulfate (Gyp) Index 158,400

Below 500,000 Remote / 500,000 - 10,000,000 Possible / Above 10,000,000 Probable

*This Calculation is only an approximation and is only valid before treatment of a well or several weeks after treatment.

Remarks RW 1.40 @72F


Report # 844

505 796 9072

OCT-15-01 MON

38 Laboratory Services

P. 02

**Laboratory Services, Inc.**

4016 Fiesta Drive
Hobbs, New Mexico 88240

Telephone: (505) 397-3713

FOR: Devon/SFS Operating Inc.
P. O. Box 250
Artesia, New Mexico 88211-0250

SAMPLE:
IDENTIFICATION: Bell Lake #22
COMPANY: Devon/SFS
LEASE:
PLANT:

SAMPLE DATA: DATE SAMPLED: 10/14/01
ANALYSIS DATE: 10/15/01
PRESSURE - PSIG 680
SAMPLE TEMP. °F 78
ATMOS. TEMP. °F

GAS (XX) LIQUID ()
SAMPLED BY: R. Hicks-Pro Well
ANALYSIS BY: Vickie Biggs

REMARKS: Sample taken @ the meter run.

COMPONENT ANALYSIS

COMPONENT	MOL PERCENT	GPM
Hydrogen Sulfide (H2S)		
Nitrogen (N2)	0.557	
Carbon Dioxide (CO2)	0.449	
Methane (C1)	95.878	
Ethane (C2)	2.345	0.626
Propane (C3)	0.584	0.161
I-Butane (IC4)	0.099	0.032
N-Butane (NC4)	0.145	0.046
I-Pentane (IC5)	0.066	0.024
N-Pentane (NC5)	0.053	0.019
Hexane Plus (C6+)	0.324	0.141
	100.000	1.049

BTU/CU.FT. - DRY 1048
AT 14.650 DRY 1044
AT 14.650 WET 1026
AT 14.73 DRY 1050
AT 14.73 WET 1032

MOLECULAR WT. 17.1423

SPECIFIC GRAVITY -
CALCULATED 0.591
MEASURED