

APPLICATION TO DRILL
 POGO PRODUCING COMPANY
 WBR FEDERAL # 7
 UNIT "K" SECTION 13
 T22S-R32E LEA CO. NM

In response to questions asked under Section II of Bulletin NTL-6 the following information on the above well is provided for your consideration.

1. Location: 1980' FSL & 2310' FWL SEC. 13 T22S-R32E LEA CO. NM
2. Elevation above Sea Level: 3702' GR.
3. Geologic name of surface formation: Quaternary Aeolian Deposits.
4. Drilling tools and associated equipment: Conventional rotary drilling rig using drilling mud as a circulating medium for solids removal from hole.
5. Proposed drilling depth: 10,200'
6. Estimated tops of geological markers:

Rustler Anhydrite	900'	Cherry Canyon	6000'
Basal Anhydrite	4500'	Brushy Canyon	7000'
Delaware	4842'	Bone Spring	8730'
Ramsey Sand	4920'	1st Bone Spring Sand	9850'
7. Possible mineral bearing formations:

Delaware	Oil	Brushy Canyon	Oil
Cherry Canyon	Oil	Bone Spring	Oil
8. Casing program:

Hole size	Interval	OD of casing	Weight	Thread	Collar	Grade
25"	0-40	20"	NA	NA	NA	Conductor
17½"	0-1000'	13 3/8"	48	8-R	ST&C	H-40
12½"	0-4700'	8 5/8"	32	8-R	ST&C	J-55 S-80
7 7/8"	0-10,200'	5½"	17	8-R	LT&C	N-80 J-55