

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. TYPE OF WORK <div style="display: flex; justify-content: space-around;"> DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> </div>			7. UNIT AGREEMENT NAME <div style="border: 1px solid black; height: 20px; width: 100%;"></div>		
b. TYPE OF WELL <div style="display: flex; justify-content: space-between;"> <div> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> </div> <div> OTHER <input type="checkbox"/> </div> </div>			<div style="display: flex; justify-content: space-between;"> <div>SINGLE ZONE <input checked="" type="checkbox"/></div> <div>MULTIPLE ZONE <input type="checkbox"/></div> </div>		
2. NAME OF OPERATOR <div style="display: flex; justify-content: space-between;"> POGO PRODUCING COMPANY (RICHARD WRIGHT 915-685-8140) </div>			8. FARM OR LEASE NAME, WELL NO. LIVINGSTON RIDGE "19" Federal # 3		
3. ADDRESS AND TELEPHONE NO. P.O. BOX 10340 MIDLAND, TEXAS 79702-7340 (915-695-8100)			9. API WELL NO. 30-225-36029		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)* At surface 2150' FSL & 330' FWL SEC. 19 T22S-R32E LEA CO. NM At proposed prod. zone SAME			10. FIELD AND POOL, OR WILDCAT LIVINGSTON RIDGE-DELAWARE		
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE* Approximately 25 miles East of Carlsbad New Mexico.			11. SEC., T., R. M., OR BLK. AND SURVEY OR AREA Section 19 T22S-R32E		
15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any) 330'		16. NO. OF ACRES IN LEASE 280		17. NO. OF ACRES ASSIGNED TO THIS WELL 40	
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 1800'		19. PROPOSED DEPTH 8700'		20. ROTARY OR CABLE TOOLS ROTARY	
21. ELEVATIONS (Show whether DF, RT, GR, etc.) 3587' GR.			22. APPROX. DATE WORK WILL START* WHEN APPROVED		

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	GRADE SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
25"	Conductor	NA	40'	Cement to surface with Redi-mix.
17½"	H-40 13 3/8"	48	800'	800 Sx. circulate cement to surface
11"	J-55 8 5/8"	32	4400'	1500 Sx. " " " "
7 7/8"	J-55 5½"	17 & 15.5	8700'	1650 Sx. " " " "

1. Drill 25" hole to 40'. Set 40' of 20" conductor and cement to surface with Redi-mix.
2. Drill 17½" hole to 800'. Run and set 800' of 13 3/8" 48# H-40 ST&C casing. Cement with 800 Sx. of Class "C" cement + 2% CaCl, + ¼# Flocele/Sx. Circulate cement to surface.
3. Drill 11" hole to 4400'. Run and set 4400' of 8 5/8" 32# J-55 ST&C casing. Cement with 1500 Sx. of Class "C" cement + additives, circulate cement to surface.
4. Drill 7 7/8" hole to 8700'. Run and set 8700' of 5½" casing as follows: 2500' of 5½" 17# J-55 LT&C, 5200' of 5½" 15.5# J-55 LT&C, 1000' of 5½" 17# J 55 LT&C casing. Cement in 3 stages. DV tools at 6100' & 3700'±. Cement 1st stage with 650 Sx. of Class "H" cement + additives, 2nd stage cement with 600 Sx. of Class "C" cement + additives, cement 3rd stage with 400 Sx. of Class "C" + additives circulate cement to surface.

**APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED**

ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen, give data on present depth, present near-surface geology, and present magnetic zone. If proposal is to drill or open directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give show logs.

SIGNED APR 1 JAMES TITLE Agent

DATE 09/18/02

(This space for Federal or State office use)

PERMIT NO. _____ APPROVAL DATE _____

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject land.

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY _____ /S/ JOE G. LARA

333

FIELD MANAGER

—

OCT 16 2002

***See Instructions On Reverse Side**

APPROVAL FOR 1 YEAR

18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

DISTRICT I
P.O. Box 1980, Hobbs, NM 88241-1980

DISTRICT II
P.O. Drawer DD, Artesia, NM 88211-0719

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
P.O. BOX 2088, SANTA FE, N.M. 87504-2088

State of New Mexico
Energy, Minerals and Natural Resources Department
OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-102
Revised February 10, 1994
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-025 36029	Pool Code 39360	Pool Name LIVINGSTON RIDGE-DELAWARE
Property Code 30-6-16	Property Name LIVINGSTON RIDGE 19 FEDERAL	Well Number 3
OGRID No. 17891	Operator Name POGO PRODUCING COMPANY	2987' 3587'



Surface Location

UL or lot No. 3	Section 19	Township 22-S	Range 32-E	Lot Idn	Feet from the 2150'	North/South line SOUTH	Feet from the 330'	East/West line WEST	County LEA
---------------------------	----------------------	-------------------------	----------------------	---------	-------------------------------	----------------------------------	------------------------------	-------------------------------	----------------------

Bottom Hole Location If Different From Surface


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Dedicated Acres 40	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

LOT 1						OPERATOR CERTIFICATION I hereby certify the the information contained herein is true and complete to the best of my knowledge and belief.  Signature Joe T. Janica Printed Name Agent Title 09/18/02 Date
44.70 AC LOT 2						
44.75 AC LOT 3 SEE DETAIL						
44.79 AC LOT 4						
44.84 AC						SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. SEPTEMBER 10, 2002 Date Surveyed Signature & Seal of Professional Surveyor  Certificate No. RONALD J. EDISON 3239 GARY EDISON 12641

DETAIL
3589.3' 3588.7'
3583.3' 3586.0'
330'
2150'

VICINITY MAP



SCALE: 1" = 2 MILES

SEC. 19 TWP. 22-S RGE. 32-E

SURVEY N.M.P.M.

COUNTY LEA

DESCRIPTION 2150' FSL & 330' FWL


ELEVATION 3587'

OPERATOR POGO PRODUCING COMPANY

LEASE LIVINGSTON RIDGE 19 FEDERAL

JOHN WEST SURVEYING
HOBBS, NEW MEXICO
(505) 393-3117

LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL: 10'

SEC. 19 TWP. 22-S RGE. 32-E

BOOTLEG RIDGE, N.M.

SURVEY N.M.P.M.

THE DIVIDE, N.M.

COUNTY LEA

DESCRIPTION 2150' FSL & 330' FWL

ELEVATION 3587'

JOHN WEST SURVEYING
HOBBS, NEW MEXICO
(505) 393-3117

OPERATOR POGO PRODUCING COMPANY

LEASE LIVINGSTON RIDGE 19 FEDERAL

U.S.G.S. TOPOGRAPHIC MAP

BOOTLEG RIDGE, & THE DIVIDE, N.M.

APPLICATION TO DRILL

POGO PRODUCING COMPANY
 LIVINGSTON RIDGE "19" FEDERAL # 3
 LOT # 3 SECTION 19
 T22S-R32E LEA CO. NM

In response to questions asked under Section II of Bulletin NTL-6 the following information on the above well is provided for your consideration.

1. Location: 2150' FSL & 330' FWL SEC. 19 T22S-R32E LEA CO. NM
2. Elevation above Sea Level: 3587' GR.
3. Geologic name of surface formation: Quaternary Aeolian Deposits.
4. Drilling tools and associated equipment: Conventional rotary drilling rig using drilling mud as a circulating medium for solids removal from hole.
5. Proposed drilling depth: 8700'
6. Estimated tops of geological markers:

Basal Anhydrite	4240'	Cherry Canyon	5390'
Delaware Lime	4515'	Brushy Canyon	6630'
Bell Canyon	4540'	Bone Spring	8400'
7. Possible mineral bearing formations:

Delaware Lime	Oil
Bone Spring	Oil
8. Casing program:

Hole size	Interval	OD of casing	Weight	Thread	Collar	Grade
25"	0-40'	20"	NA	NA	NA	Conductor
17½"	0-800'	13 3/8"	48	8-R	ST&C	H-40
11"	0-4400'	8 5/8"	32	8-R	ST&C	J-55
7 7/8"	0-8700'	5½"	17 & 15.5	8-R	LT&C	J-55

APPLICATION TO DRILL

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM

9. CEMENTING & SETTING DEPTH:

20"	Conductor	Set 40' of 20" conductor and cement to surface with Redi-mix.
13 3/8"	Surface	Set 800' of 13 3/8" 48# H-40 ST&C casing. Cement with 800 Sx. of Class "C" cement + 2% CaCl ₂ + 1/4# Flocele/Sx. Circulate cement to surface.
8 5/8"	Intermediate	Set 4400' of 8 5/8" 32# J-55 ST&C casing. Cement with 1500 Sx. of Class "C" cement + additives, circulate cement to surface.
5 1/2"	Production	Set 8700' of 5 1/2" casing as follows: 2500' of 5 1/2" 17# J-55 LT&C, 5200' of 5 1/2" 15.5# J-55 LT&C, 1000' of 5 1/2" 17# J-55 LT&C. Cement in 3 stages with DV tools at 6100' & 3700'±. Cement 1st stage with 650 Sx. of Class "H" cement + additives, 2nd stage cement with 600 Sx. of Class "C" cement + additives, 3rd stage cement with 400 Sx. of Class "C" cement + additives, circulate cement to surface.

10. PRESSURE CONTROL EQUIPMENT: Exhibit "E" shows a 900 Series 3000 PSI working pressure B.O.P. consisting of an annular bag type preventor, middle blind rams and bottom pipe rams. The B.O.P. will be nipped up on the 13 3/8" casing and tested to API specifications. The B.O.P. will be operated at least once in each 24 hour period and the blind rams will be operated when drill pipe is out of hole on trips. Full opening stabbing valve and upper kelly cock will be utilized. Exhibit "E-1" shows a hydraulically operated closing unit and a 2" 3000 PSI choke manifold with dual adjustable chokes. No abnormal pressures or temperatures are expected.

11. PROPOSED MUD CIRCULATING SYSTEM:

DEPTH	MUD WT.	VISC.	FLUID LOSS	TYPE MUD SYSTEM
40-800'	8.5-8.6	29-34	NC	Fresh water spud mud add paper to control seepage.
800-4400'	10.0-10.3	29-36	NC	Brine water use paper to control seepage and high viscosity sweeps to clean hole.
4400-8700	8.5-8.7	29-38	NC	Fresh water use fresh water Gel for viscosity control use high viscosity sweeps to clean hole. If water loss control is needed use a Polymer system.

Sufficient mud materials will be kept on location at all times in order to combat lost circulation, or unexpected kicks. In order to run DST's, open hole logs, and casing viscosity and/or water loss may have to be adjusted to meet these needs.

APPLICATION TO DRILL

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM

12. TESTING, LOGGING, & COREING PROGRAM:

- A. Open hole logs: Dual Induction, SNP, CNL, LDT, Gamma Ray, Caliper from TD to 4400'.
- B. Cased hole logs: Gamma Ray, Neutron from 4400' to surface and Collar locator log over the productive interval.
- C. Mud logger will be put on hole at 4400' and remain on hole to TD.
- D. No cores or DST's are planned at this time.

13. POTENTIAL HAZARDS:

No abnormal pressures or temperatures are expected. Hydrogen Sulfide gas may be encountered, H₂S detectors will be in place to detect any presence of unsafe levels of H₂S. No lost circulation is expected to occur. All personnel will be familiar with all aspects of safe operations of all equipment that will be used. Estimated BHP 3800 PSI & estimated BHT 165°.

14. ANTICIPATED STARTING DATE AND DURATION OF OPERATION:

Roads and location construction will begin after the BLM approves the APD. Anticipated spud date will be as soon as pad & road construction has been completed. Drilling time for the well is estimated to take 29 days. If production casing is run an additional 30 days will be required to complete well and construct surface facilities.

15. OTHER FACETS OF OPERATION:

After running production casing, cased hole Gamma-Neutron & Collar logs will be run over all possible pay intervals. If commercial production from the Bone Spring pay is indicated it will be perforated and stimulated. Then if necessary the pay will be swab tested and completed as an oil well.

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

1. All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:
 - A. Characteristics of H₂S
 - B. Physical effects and hazards
 - C. Proper use of safety equipment and life support systems.
 - D. Principle and operation of H₂S detectors, warning system and briefing areas.
 - E. Evacuation procedure, routes and first aid.
 - F. Proper use of 30 minute pressure demand air pack.
2. H₂S Detection and Alarm Systems
 - A. H₂S detectors and audio alarm system to be located at bell nipple, end of blooie line (mud pit) and on derrick floor or doghouse.
3. Windsock and/or wind streamers
 - A. Windsock at mudpit area should be high enough to be visible.
 - B. Windsock at briefing area should be high enough to be visible.
 - C. There should be a windsock at entrance to location.
4. Condition Flags and Signs
 - A. Warning sign on access road to location.
 - B. Flags to be displayed on sign at entrance to location. Green flag, normal safe condition. Yellow flag indicates potential pressure and danger. Red flag, danger, H₂S present in dangerous concentration. Only emergency personnel admitted to location.
5. Well control equipment
 - A. See exhibit "E" & "E-1"
6. Communication
 - A. While working under masks chalkboards will be used for communication.
 - B. Hand signals will be used where chalk board is inappropriate.
 - C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephoned will be available at most drilling foreman's trailer or living quarters.
7. Drillstem Testing
 - A. Exhausts will be watered.
 - B. Flare line will be equipped with an electric ignitor or a propane pilot light in case gas reaches the surface.
 - C. If the location is near to a dwelling a closed DST will be performed.

HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

8. Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.
9. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

SURFACE USE PLAN

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM

1. EXISTING ROADS: Area maps, Exhibit "B" is a reproduction of a County General Highway Map. Exhibit "C" is a reproduction of a USGS Topographic Map, showing existing roads and proposed roads. All existing roads will be maintained in a condition equal to or better than current conditions. Any new roads will be constructed to BLM specifications.
 - A. Exhibit "A" shows the proposed well site as staked.
 - B. From Hobbs New Mexico take U.S. Hi-way 62-180 west toward Carlsbad NM, go 38 miles to CR-29 turn South go 14 miles to Mills Ranch Road turn Left (East) follow road 1.8 miles to location on the North side of road.
 - C. If tank battery is not built on location flowlines will be laid along road R-O-W to an existing tank battery, see Exhibit "F".
2. PLANNED ACCESS ROADS: No new road will be necessary.
 - A. The access road will be crowned and dirched to a 12'00" wide travel surface with a 40' right-of-way.
 - B. Gradient on all roads will be less than 5.00%.
 - C. Turnouts will be constructed as needed.
 - D. If needed, road will be surfaced with a minimum of 4" of caliche. This material will be obtained from a local source.
 - E. Centerline for the new access road has been flagged. Earthwork will be as required by field conditions.
 - F. Culverts in the access road will not be used. The road will be constructed to utilize low water crossings for drainage as required by the Topography.
3. LOCATION OF EXISTING WELLS IN A ONE-MILE RADIUS EXHIBIT "A-1"

A. Water wells	-	None known
B. Disposal wells	-	None known
C. Drilling wells	-	None Known
D. Producing wells	-	As shown on Exhibit "A-1"
E. Abandoned wells	-	As shown on Exhibit "A-1"

SURFACE USE PLAN

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM

4. If on completion this well is a producer the operator will lay pipelines and construct powerlines along existing road R-O-W's or other existing R-O-W's. Possible routes of pipelines, flowlines and powerlines are shown on Exhibit "F".

5. LOCATION AND TYPE OF WATER SUPPLY:

Water will be purchased locally from a commercial source and trucked over the access roads or piped to location in flexible lines laid on top of the ground.

6. SOURCE OF CONSTRUCTION MATERIAL:

If possible construction material will be obtained from the excavation of drill site, if additional material is needed it will be obtained from a local source and transported over the access roads as shown on Exhibit "C".

7. METHODS OF HANDLING WASTE MATERIAL:

- A. Drill cuttings will be disposed of in the reserve pits.
- B. All trash, junk and other waste material will be contained in trash cages or trash bins to prevent scattering. When the job is completed all contents will be removed and disposed of in a approved sanitary land fill.
- C. Salts remaining after completion of well will be picked up by the supplier, including broken sacks.
- D. Waste water from living quarters will be drained into holes with a minium of 10'. These holes will be covered during drilling and will be back filled when the well is completed. A Porto-John will be provided for the rig crews. This equipment will be properly maintained during the drilling and completion operations and will be removed when all operations are complete.
- E. Remaining drilling fluids will be allowed to evaporate in the reserve pits until the pits are dry enough to be broken out for furthed drying. If the drilling fluids do not evaporate in a reasonable time they will be hauled off by transports to a state approve disposal site. Later pips will be broken out to speed drying. Water produced during completion will be put in reserve pits. Oil and condensate produced will be put in storage tanks and sold.

8. ANCILLARY FACILITIES:

- A. No camps or air strips will be constructed on location.

SURFACE USE PLAN

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM

9. WELL SITE LAYOUT:

- A. Exhibit "D" shows the proposed well site layout.
- B. This exhibit indicated proposed location of reserve and sump pits and living facilities.
- C. Mud pits in the active circulating system will be steel pits & the reserve pit is proposed to be unlined unless subsurface condition encountered during pit construction indicate that lining is needed for lateral containment of fluids.
- D. If needed, the reserve pit is to be lined with polyethelene. The pit liner will be 6 mils thick. Pit liner will extend a minimum of 2'00" over the reserve pits dikes where the liner will be anchored down.
- E. The reserve pit will be fenced on three sides with four strands of barbed wire during drilling and completion phases. The fourth side will be fenced after all drilling operations have ceased. If the well is a producer, the reserve pit fence will be torn down. The reserve pit and those areas of the location not essential to production facilities will be reclaimed and seeded per BLM requirements.

10. PLANS FOR RESTORATION OF SURFACE:

Rehabilitation of the location and reserve pit will start in a timely manner after all drilling operations cease. The type of reclamation will depend on whether the well is a producer or a dry hole.

However, in either event, the reserve pit will be allowed to dry properly, and fluid removed and disposed of in accordance with Article 7.B as previously noted. The pit area will then be leveled and contoured to conform to the original and surrounding area. Drainage systems, if any, will be reshaped to the original configuration with provisions made to alleviate erosion. These may need to be modified in certain circumstances to prevent inundation of the location's pad and surface facilities. After the area has been shaped and contoured, topsoil from the spoil pile will be placed over the disturbed area to the extent possible. Revegetation procedures will comply with BLM standards.

If the well is a dry hole, the pad and road area will be contoured to match the existing terrain. Topsoil will be spread to the extent possible. Revegetation will comply with BLM standards.

Should the well be a producer, the previously noted procedures will apply to those areas which are not required for production facilities.

SURFACE USE PLAN

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM

11. OTHER INFORMATION:

- A. Topography is relatively flat with a slight dip to the East, with shallow drainage patterns. Vegetation consists of creosote bush, little leaf sumac, broom-snakeweed, and native grasses.
- B. Surface is owned by the U.S. Department of Interior and is administered by the Bureau of Land Management. The surface is leased to ranchers for grazing of live stock.
- C. An archaeological survey will be conducted and the results will be filed with The Bureau of Land Management Carlsbad Field office in Carlsbad NM.
- D. There are no domestic dwellings located within one mile of the location.

12. OPERATORS REPRESENTATIVE:

Before construction:


TIERRA EXPLORATION, INC.
P.O. BOX 2188
HOBBS, NEW MEXICO 88241
JOE T. JANICA
OFFICE PHONE 505-391-8503

During and after construction:

POGO PRODUCING COMPANY
P.O. BOX 10340
MIDLAND, TEXAS 79702-7340
RICHARD WRIGHT
OFFICE PHONE 915-685-8140

13. CERTIFICATION: I hereby certify that I or persons under my direct supervision have inspected the proposed drill site and access route, that I am familiar with the conditions which currently exist, that the statements made in this plan are to the best of my knowledge, are true and correct, and that the work associated with the operations proposed herein will be performed by POGO PRODUCING COMPANY it's contractors/subcontractors is in the conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provision of U.S.C. 1001 for the filing of a false statement.

NAME : Joe T Janica
DATE : 09/18/02
TITLE : Agent







EXHIBIT "B"
LOCATION & ACCESS ROAD MAP


POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM



- △ Wind Direction Indicators (wind sock or streamers)
- △ H2S Monitors (alarms at bell nipple and shale shaker)
- Briefing Areas
- Remote BOP Closing Unit
- Sign and Condition Flags

EXHIBIT "D"
RIG LAY OUT PLAT

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM



ARRANGEMENT SRRA

900 Series
3000 PSI WP

EXHIBIT "E"
SKETCH OF B.O.P. TO BE USED ON

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM




FIGURE K4-1. Typical choke manifold assembly for 2M and 3M rated working pressure service — surface installation.




FIGURE K6-1. The schematic sketch of an accumulator system shows required and optional components.

EXHIBIT "E-1"
CHOKE MANIFOLD & CLOSING UNIT

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM




EXHIBIT "F"
ROUTE OF
FLOWLINE & POWERLINE

POGO PRODUCING COMPANY
LIVINGSTON RIDGE "19" FEDERAL # 3
LOT # 3 SECTION 19
T22S-R32E LEA CO. NM