

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC
MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with appropriate recommendations considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOMidland, Texas
(Place)September 2, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the New Mexico State LeaseSeaboard Oil Company

(Company or Operator)

Well No. 1 in 00
(Unit)SW 1/4 SE 1/4 of Sec. 13, T. 21, R. 33, NMPM., Wildcat Pool

(40-acre Subdivision)

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to plug and abandon the above described well at a depth of 5000' on September 2, 1956. The hole will be loaded with a heavy mud laden fluid after electrical logs are run. A cement plug of 20 sacks will be placed from approximately 3895' to 3945'. Another cement plug will be placed from approximately 1790' to 1870'. The 9-5/8" OD surface casing which is set at 1830.39' will be left in the hole as it is cemented to the surface. A 10 sack cement plug will be placed in the 9-5/8" OD surface casing at the surface and a steel plate will be welded over the top of the casing. A 1/2" hole will be cut in the casing below the steel plate. A 4" OD by 4" long steel marker will be welded to the steel plate.

Approved SEP 6 1956, 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy C. M. LuederTitle Engineer District 1Seaboard Oil Company

Company or Operator

By F. M. LoopPosition District Superintendent

Send Communications regarding well to:

Name F. M. LoopAddress Box 352, Midland, Texas