

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	35	35	Caliche
35	70	35	Red Sand
70	95	25	" "
95	120	25	" "
120	185	65	Red Shale
185	200	15	" "
200	215	15	Shale
215	230	15	Blue Shale and Sand
230	365	135	Red Shale
365	375	10	Blue Sandy Shale
375	395	20	Brown Shale
395	400	5	Shale
400	420	20	Brown Shale
420	460	40	" "
460	600	140	Red Shale
600	630	30	Brown Shale
630	660	30	Red Shale
660	680	20	" "
680	765	85	Brown Shale
765	775	10	Brown Shale & Sand
775	805	30	Line & Blue Shale
805	845	40	Brown Shale
845	855	10	" "
855	885	30	Red Sandy Shale
885	930	45	Brown Sandy Shale
930	970	40	Brown Shale
970	1005	35	" "
1005	1020	15	Water Sand
1020	1035	15	Red Sand and Shale
1035	1170	135	Red Sand - Water
1170	1330	160	Red Bed
1330	1350	20	Broken Shale
1350	1700	350	Red Rock
1700	1775	75	Anhydrite
1775	1860	85	Anhydrite
1860	1930	70	Salt
1930	1950	20	Anhydrite
1950	1980	30	Salt
1980	2015	35	Anhydrite & Line
2015	2065	50	Salt and Red Bed
2065	2130	65	Salt, Anhydrite and Red Bed
2130	2240	110	Salt and Potash
2240	2335	95	Salt, Anhydrite and Potash
2335	2410	75	Salt and Potash
2410	2455	45	Salt and Anhydrite
2455	2855	400	Salt and Potash
2855	2890	35	Anhydrite
2890	3090	200	Salt
3090	3120	30	Anhydrite
3120	3375	255	Salt and Potash
3375	3400	25	Anhydrite
3400	3435	35	Salt and Anhydrite
3435	3535	110	Salt
3535	3575	40	Anhydrite
3575	3630	55	Buff Lime
3630	3645	15	" " trace Sand and Shale
3645	3758	113	Buff Lime
3758 =	3754		Steel Line Measurement