

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Fort Worth, Texas
(Place)

September 26, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

WILLIAM A. & EDWARD R. HUDSON..... **AMERADA-STATE**..... Well No. **2**..... in **E**..... (Unit)
(Company or Operator)
SW $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **26**....., T. **21S.**....., R. **33E.**....., NMPM., **Wildcat**..... Pool
(40-acre Subdivision)
Lea..... County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Pursuant to telephone approval of September 9, 1956, we intend to plug and abandon the above well at a total depth of 4125'. We intend to run tubing to 4120' and set a 50-sack cement plug. We will then pull the tubing up to 3750' and set a 25-sack cement plug, then pull the tubing to 3600' and pump in 40 sacks of Gel. We will then pull the tubing to 1800' and set a 50-sack cement plug and pull the tubing out. We will then pull the 8-5/8" casing and place a 15-sack cement plug at 800'. We will then pull the 10-3/4" casing and the 13-3/8" casing, and put a cement bridge at 65' and cement to the top of the hole. We will cement in a 4" steel marker in the top of the hole and the pits will be filled and the grounds cleaned and left in the original condition.

Approved..... **SEP 28 1956**....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

WILLIAM A. & EDWARD R. HUDSON

Company or Operator
By.....

Position..... **Partner**
Send Communications regarding well to:

Name..... **Edward R. Hudson**.....

Address..... **1810 Electric Building**
Fort Worth, Texas