

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-1167

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Temp. Abandon	7. Unit Agreement Name
2. Name of Operator WILSON OIL COMPANY	8. Farm or Lease Name Shell-State B-1167
3. Address of Operator P.O.Box 457 Artesia, New Mexico 88210	9. Well No. 13
4. Location of Well UNIT LETTER H , 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 21 RANGE 34 NMPM.	10. Field and Pool, or Wildcat Wilson (Y-7R)
15. Elevation (Show whether DF, RT, GR, etc.) 3665' Gr.	12. County Los

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**Top Pay 3748'; Total depth 4139'; Plugged back 3770' 16" 120' with 80 sx. 7" at 3542';
5 1/2" 3930' with 200 sx;**

Propose to plug and abandon well as follows;

**25 sx cement plug to cover perfs. 3744-3752'
25 sx cement plug at top 7" casing if shot off and pulled.
25 sx cement plug at base of 16" casing at 110'.
15 sx cement plug at surface with regulation marker.
8 1/4 native mud between cement plugs.**

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *N. R. Lamb* **N.R. Lamb** TITLE **Vice President** DATE **3-12-71**

APPROVED BY *Joe D. Ramsey* **Joe D. Ramsey** TITLE Dist. I. Supv. DATE **OCT 18 1971**
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

001 181971

OIL CONSERVATION COMM.

HOBBS, H. L.

2-23-71