

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE

AREA 400 ACRES
LOCATE WELL CORRECTLY

WILSON OIL COMPANY

Santa Fe, New Mexico (P.O.Box 627)

Address

State No. B-6807

Well No. 11

in ~~Swamp~~

of Sec. 13

T. 21 S

R. 34E

West Eunice

Field, Lea

County.

Well No. 1980

1000 south of the North line and 4620 feet west of the East line of Section 13

If State land the oil and gas lease is No. B-6807

Assignment No.

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Address

Drilling commenced Feb. 24

19 44

Drilling was completed

May 11

19 44

Name of drilling contractor our own tools

Address

Elevation above sea level at top of casing 3672 feet.

The information given is to be kept confidential until

No

OIL SANDS OR ZONES

No. 1 from None

No. 4, from

No. 2 from

No. 5, from

No. 3, from

No. 6, from

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 240 to 290 feet

No. 2, from 880 to 945 feet

Hole full

No. 3, from

No. 4, from

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER FOOT	MAKE	AMOUNT	KIND OF SHOE	CUT & TAPPED FROM	IDENTIFIED	PURPOSE
16	70	10	Second hand	110	Plain			
All other strings recovered								

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	NO. GRAVITY	AMOUNT OF MUD USED
18	16	110	120	Balliburton		
All other strings recovered						

PLUGS AND ADAPTERS

Heaving plug Material Length Depth Set
Adapters Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment None

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 3860 feet, and from feet to feet

PRODUCTION

Put to producing None 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water, and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

Chas. Quinn Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 22nd

Santa Fe, New Mexico

Place

Date

day of May 19 44

Name

Position President

Representing WILSON OIL COMPANY

Company or Employer

My Commission expires July 12, 1945

Address P.O.Box 627, Santa Fe, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	12	12	Caliche
12	109	97	Sand
109	240	131	Rock and shale
240	275	35	Water sand
275	880	605	Red beds- rock and shales
880	945	65	Sand - water
945	1020	75	Red rock- some sand
1020	1090	70	Blue shale
1090	1125	35	Sandy shale
1125	1255	130	Red rock
1255	1652	397	Red rock some shale
1652	1800	148	Anhydrite S.L. M.
1800	1885	85	Salt
1885	1910	25	Anhydrite
1910	2130	220	Salt-Anhydrite and streaks of red rock
2130	2290	160	Salt and potash
2290	2375	85	Anhydrite
2375	2925	550	Salt and potash
2925	2937	12	Blue shale (blue mud)
2937	3090	153	Salt and Anhydrite
3090	3135	45	Salt and potash
3135	3450	115	Anhydrite (S.L.M.) Hole reduced at 3440- 8" to 6"
3450	3525	75	Grey Lime (probably brown lime at approx. 3450)
3525	3550	25	Grey and sandy lime- Gas pop up at 3552
3550	3600	50	Lime- Gas at 3580
3600	3675	75	Lime-sandy-Gas at 3610
3675	3782	107	Lime-Small show oil at 3782- No live oil in hole
3782	3880	98	Lime- show oil at 3840 to 3850- Sulphur water at 3860
			Hole plugged and abandoned