

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)March 4, 1957  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Cities Service Oil Company  
(Company or Operator)

State V

Well No. 2 in H  
(Unit)NE 1/4 SE 1/4 of Sec. 16, T. 21S, R. 34E, NMPM., West Wilson Pool  
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was completed in 1951 at a total depth of 3914'. It was potentialled for 8.75 barrel of oil. Production has declined to a point where it is no longer economical to continue operations. Production for February 1957 was 63 barrel or 2.25 barrel per day. Consideration has been given to remedial possibilities and none seems feasible since the pay section is thin and water production has increased to 93%.

It is proposed to plug and abandon the well by reclaiming all possible 5 1/2" casing, loading hole with mud, spotting 10 sacks of cement to plug off the open hole, spotting 25 sacks at the point where 5 1/2" casing is shot off, spotting 40 sacks of cement above the salt section extending into the 8 5/8" casing at the bottom and spot 10 sacks in the top of 8 5/8" casing leaving a 4" pipe 4' above the surface as a marker.

Approved....., 19.....  
Except as follows:Cities Service Oil Company  
Company or Operator

By.....

Position..... District Superintendent

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By..... E. Fischer

Name..... Geo. M. Geyer

Title.....

Address..... Box 97, Hobbs, New Mexico