

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
SEP 26 1945

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Roswell, New Mexico

Sept. 20, 1945

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

The Vickers Petro. Co. Inc. Shell-State Well No. 1 in the _____
Company or Operator LeaseCNW NE 1/4 of Sec. 17, T. 21S, R. 34E, N. M. P. M.,
Wildcat Field, Lea County.

The dates of this work were as follows: Sept. 1 to 6 inc.

Notice of intention to do the work was (was not) submitted on Form C-102 on Aug. 31, 1945
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We plugged the bottom of the hole with eight sacks of cement followed with 5 sacks of mud followed with 7 sacks of cement. The hole was then filled with mud to the depth of 3750' where a plug of 10 sacks of cement was set. The top 788' of 7" casing was pulled after the hole had been filled with mud to a depth of 1906' and a 10 sack cement plug set. After pulling the 7" casing, the hole was filled with mud to the surface and then bailed down to a depth of 300' where a plug of 5 sacks of cement was set. The hole was then filled with mud to the surface. The surface of the hole was then cemented and a regulation marker set.

Witnessed by Stanley Carper Carper Drlg. Co. Supt.
Name Company Title

Subscribed and sworn before me this 20th

I hereby swear or affirm that the information given above is true and correct.

day of September, 1945

Name Edward L. Bunte

Position Geological Engineer

Notary Public

Representing The Vickers Petro. Co. Inc.
Company or Operator

My commission expires October 2, 1945

Address Roswell, New Mexico

Remarks:

Roy Yarbrough
Oil & Gas Inspector

Title