

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-11610	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Disposal Well		7. Unit Agreement Name
Name of Operator Coquina Oil Corporation		8. Farm or Lease Name Wilson State
Address of Operator P. O. Drawer 2960 Midland, Texas 79702		9. Well No. 19
Location of Well UNIT LETTER <u>G</u> <u>2310</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>23</u> TOWNSHIP <u>21S</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Wilson Yates Seven Rivers
11. Elevation (Show whether DF, RT, GR, etc.) 3661' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The above disposal well is no longer needed. It is therefore proposed to plug the well in the following manner. Cement plugs will be set at the following depths.

Plug #	No. Sacks	Depth
1	CIBP + 50'	+ 3600'
2	75 sxs	Squeezed out 7" csg @ + 1000' using retainer
3	50'	Left on top of retainer
4	10 sxs	at surface w/dry hole marker

The hole will be filled w/mud ladden fluid between plugs. Notice will be given so plugs may be witnessed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Steve Surley TITLE Production Engineer DATE Dec 9, 1982

APPROVED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE DEC 14 1982