

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		
NOTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>

Hobbs, New Mexico

April 27, 1942

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

**Continental Oil Co.** State J-24

Well No. 1 in NW/4

Company or Operator

Lease

of Sec. 24, T. 21-S, R. 34-E, N. M. P. M., W. Eunice Field,  
Lea County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

This well was drilled to a T.D. of 3930' in lime, on 4-25-42. On 4-26-42 swabbed 3 bbls. water per hour on a 24 hour test. On swabbing test at the following depths the well made no oil, gas or water: 3850' and 3880'. On swabbing test at 3800' well made no oil or water with a very slight show of gas.

Permission is requested to plug and abandon this well using the following procedure. Set a cement plug from T.D. 3930' to bottom of 5½" casing at 3450' and then recover as much 5½" casing as possible. Plug back inside of 5½" casing with 12# mud and set a cement plug at top of 5½" casing left in hole. Plug back with 12# mud to base of 10 3/4" casing at 417' and then plug back with cement to surface. A marker will be erected and location restored to its original condition.

APR 27 1942

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

If 5 1/2" casing is knocked off below top of salt, bridge and cement plug must set at top of salt.

Company or Operator

By \_\_\_\_\_

Position **Asst. Dist. Supt.**

Send communications regarding well to

OIL CONSERVATION COMMISSION,

By Nay Gierhous

Title \_\_\_\_\_

Name **A. B. Owen**

Address **Box CC,**

**Hobbs, New Mexico**