

A 4x4 grid with cardinal directions labeled around the perimeter: N (North) at the top, S (South) at the bottom, E (East) on the right, and W (West) on the left. The grid consists of 16 squares arranged in 4 rows and 4 columns.

Bond Status _____[illegible]

PACKER

TD

TWL

$S/$ $\mathbf{S}/$ $\mathbf{S}/$

DATE _____

ILLEGIBLE

LOG

[illegible]

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Hobbs, New Mexico

1-14-46

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Stanolind Oil & Gas Co. Mascho Unit Well No. 1 in the

SW/4 of SW/4 Company or Operator 31 of Sec. 21-S, T. 34-E, N. M. P. M.,
Wildcat Field, Lea County.
November 28, 1945

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on November 27 1945
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Mascho Unit No. 1 was plugged in following manner: Placed a 35-sx. cement plug at bottom of hole, 4308', filling back to approximately 4200', and with hole filled with heavy mud laden fluid, spotted a 15-sx. cement plug in bottom of 9-5/8" casing set at 1867' w/ 250 sacks. Approximately 870' of this casing was recovered and a 15-sack plug set in top of 13-3/8" surface casing set at 210' cemented to surface with 200 sacks. This string was left intact, and a 4" pipe marker was set in cement to extend 5' above ground level. Cellar & pits have been filled, and the location leveled to conform with surrounding terrain.

Witnessed by C. V. Campbell Stanolind Oil & Gas Co. Production Foreman.
Name Company Title

Subscribed and sworn before me this 14thday of January, 1946

Notary Public

4-23-49

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name Reep L. Hendricks
Position Field Superintendent

Representing Stanolind Oil & Gas Co.
Company or Operator

Address Hobbs, N. Mex.

Remarks:

Notary Public
Name
Title