## NEW "EXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL



Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instruction in Rules and Regulations of the Commission.

|                              | Hobbs, New Maxico    | September 18, 1945 |
|------------------------------|----------------------|--------------------|
| OIL CONSERVATION COMMISSION. | Place                | Date               |
| Santa Fe, New Mexico.        | 1<br>1<br>Marine and |                    |

Gentlemen:

|             | 51                 |          | Company<br>21-S | or C  | perator<br><b>54-E</b> |                    | Nascho<br>. P. M., | vildcat                   |                    | Well N         |                  | Lei    |                     |                |               | <u>.</u>  |
|-------------|--------------------|----------|-----------------|-------|------------------------|--------------------|--------------------|---------------------------|--------------------|----------------|------------------|--------|---------------------|----------------|---------------|-----------|
| of Sec.     | N.                 | ., T<br> |                 | -, R. | The w                  | ell is             | 660<br>the         | feet                      | (N.)               | ( <b>Š</b> .)  | of the           | South  | line                | and            | 7             | 50 feet   |
|             |                    |          |                 |       | (Give<br>If stat       | location<br>e land | the oil and        | tion or oth<br>d gas leas | ner leg<br>se is N | al subd<br>B-1 | livisior<br>0626 | lines. | Cross ou<br>signmen | t wron<br>t No | ıg di         | rections) |
|             |                    |          |                 |       |                        |                    | it land the        |                           |                    |                |                  |        |                     |                |               |           |
| <del></del> |                    |          |                 |       |                        |                    | s                  |                           |                    |                |                  |        |                     |                |               |           |
| LOCAT       | REA 640<br>TE WELL | COF      | RECTLY          |       |                        |                    | o drill we         |                           |                    |                |                  |        |                     | ry T           | 0 <b>01</b> / | to        |

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission On file with Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

| Size of<br>Hole              | Size of<br>Casing              | Weight Per Foot | New or<br>Second Hand | Depth                  | Landed or<br>Cemented | Sacks<br>Cement   |
|------------------------------|--------------------------------|-----------------|-----------------------|------------------------|-----------------------|-------------------|
| 17"<br>12 <del>]</del><br>7" | <b>13*</b><br>9-5/8*<br>8-5/8* | 50<br>58<br>20  | sh<br>Sh<br>New       | 2001<br>20001<br>42001 | Comen ted             | 159<br>600<br>100 |
|                              |                                |                 |                       |                        |                       |                   |

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil and gas sand should occur at a depth of about <u>4500</u> feet

19\_

Additional information: We propose to drill with rotary tools to an approximate total depth of 4500° to test the reef lime and the casing program followed as outlined above; all work in connection with drilling and completion to conform to the rules and regulations of the New Mexico Oil Conservation Commission. (Supercedes Form C-101 Filed 8-25-45)

Approved \_

except as follows:

"APPROVAL CONDITIONED DOOR COMPL. TOTO WORK REQUIREMENTS OF ONL CONT

| OIL CONSERVATION COMMISSION |
|-----------------------------|
| By Mach. Gage Specifit      |
| N .                         |
| Title                       |

Sincerely yours,

Address ...

Stanolind Old and Gas Company

Company or Operato By

Field Superintendant

Position Send communications regarding well to Ralph L. Hendrickson Name

Box "F", Hobbs, New Mexico

■ A set of the set