

DUPLICATE
 FORM C-105
 N
 [Grid for well location mapping]

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
 LOCATE WELL CORRECTLY

R. DeChicohis

State "A"

Company or Operator Lease
 Well No. 1-X in Lot #9 of Sec. 2, T. 21S
 R. 33-E, N. M. P. M., Lynch Field, Lea County.
 Well is 3637 feet south of the North line and 430 feet west of the East line of Section 2
 If State land the oil and gas lease is No. B-1573 Assignment No. 41189-C
 If patented land the owner is _____ Address _____
 If Government land the permittee is _____ Address _____
 The Lessee is R. DeChicohis Address Box 1251, Midland, Texas
 Drilling commenced April 3 1952 Drilling was completed April 30 1952
 Name of drilling contractor J. C. Clower Address Eunice, N.M.
 Elevation above sea level at top of casing 3788 feet.
 The information given is to be kept confidential until _____ 19____

OIL SANDS OR ZONES

No. 1, from 3744' to 3753' No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 95' to 115' feet. 5 B.W.P.H. - Water rose 50
 No. 2, from 920' to 975' feet. 7 B.W.P.H. - Water rose 225'
 No. 3, from _____ to _____ feet.
 No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
12 1/2"	50#	10	L.W.	159'	T.P.				Surface
6-5/8"	2 1/4#	8	Smls	3695'	T.P.				Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
18"	12 1/2"	159'	125 sx.	Halliburton		
8"	6-5/8"	3695'	325 sx.	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
 Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.
 Cable tools were used from 0 feet to 3753 feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing May 7, 1952
 The production of the first 24 hours was 860 barrels of fluid of which 10 % was oil; _____ % emulsion; 90 % water; and _____ % sediment. Gravity, Be 300
 If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

T. H. Bennett Driller W. H. Tate Driller
 P. R. Finkler Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13 _____ Midland, Texas, May 13, 1952
 day of May 1952 Name _____
 Position Owner
 Notary Public Representing R. DeChicohis
 DOROTHY F. CROUCH, Notary Public Company or Operator.
 My Commission expires _____ in and for _____ County, Texas Address Box 1251, Midland, Texas
 My Commission Expires June 1, 1953

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	30	30	Caliche
30	95	65	Hard rock
95	115	20	Gravel - 5 bailers water per hour
115	450	335	Red beds
450	920	470	Red rock
920	975	55	Water Sand - 7 B.W.P.H.
975	1200	225	Red shale
1200	1620	420	Red rock - sandy
1620	1710	90	Red rock
1710	1860	150	Anhydrite
1860	2000	140	Salt
2000	2550	550	Salt, anhydrite & red shale
2550	2900	350	Salt & potash
2900	3080	180	Salt
3080	3100	20	Anhydrite
3100	3190	90	Salt
3190	3220	30	Anhydrite
3220	3340	120	Salt
3340	3370	30	Red sand & salt
3370	3390	20	Anhydrite
3390	3530	140	Brown Lime
3530	3610	80	Sand & Lime
3610	3640	30	Hard white Lime
3640	3680	40	Lime & Sand
3680	3744	64	Hard white Lime
3744	3753	9	Soft Brown Lime - Pay