SSION

Midland, Texas

SANTA FE, NEW MEXICO

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Roles and Regulations of the Commission.

## Indicate nature of notice by checking below:

_	indicate nature of			
OTICE OF INTENTION TO TEST CASING SHUT-OFF			NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHA	ANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING		
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INT	NOTICE OF INTENTION TO PLUG WELL	
OTICE OF INTENTION TO DEP	EPEN WELL			
	Midland	i, Texas	March	10, 1952
		Place	Dat	te
IL CONSERVATION COMMISSIC	ON,			
entlemen:				
ollowing is a notice of intention	to do certain work as	s described below at the.		
R. DeChicchis				
Company or Operator	Lease			
Sec. 2 , T. 218	R. 33E	, N. M. P. M.,	ynch	Field.
	County			
मा ग	L DETAILS OF I	PROPOSED PLAN O	F WORK	
T U L.				
				~~~
FOLLOW INSTRUCTION OF THIS AND ADDRESS OF THE PROPERTY OF THE	well is 3755' emented on to ut well and f	op of anhydrite Cound junk at 3	at 3425' is ce at 1741' with 385'. Will se	mented with 100 sacks
rollow instruction of this is 25 sacks. 10" is continued to clean or ement plug from 3385 rom 1790' to 1760'	well is 3755' emented on to ut well and i 5' to 3285'. at top of Sal	o 82" casing op of anhydrite found junk at 3 will set brid to Will set 1	at 3425' is ce at 1741' with 385'. Will se ige & 30 foot c	emented with 100 sacks of 100 footement plus
otal depth of this of 25 sacks. 10" is contempted to clean or sement plug from 3385 rom 1790' to 1760' aurface pipe and put	well is 3755' emented on to ut well and i 5' to 3285'. at top of Sal	op of anhydrite found junk at 3 Will set brid t. Will set 1 on marker.	at 3425' is ce at 1741' with 385'. Will se ige & 30 foot c 0 foot cement	emented with 100 sacks of 100 footement plus
cotal depth of this 1.25 sacks. 10" is continued to clean or sement plug from 338; rom 1790' to 1760' curface pipe and put	well is 3755's mented on to ut well and f 5' to 3285'. at top of Sal up regulation	op of anhydrite found junk at 3 Will set brid t. Will set 1 on marker.	at 3425' is ce at 1741' with 385'. Will se ige & 30 foot cement.  Dechicchis	emented with 100 sacks of 100 footement plug plug in
otal depth of this 125 sacks. 10" is contempted to clean on the contempted to 1760' from 1790' to 1760' fourface pipe and put	well is 3755's mented on to ut well and f 5' to 3285'. at top of Sal up regulation	op of anhydrite found junk at 3 Will set brid t. Will set 1 on marker.	at 3425' is ce at 1741' with 385'. Will se ige & 30 foot c 0 foot cement	emented with 100 sacks of 100 footement plug in
cotal depth of this 1.25 sacks. 10" is continued to clean or sement plug from 3385 rom 1790' to 1760' apprendict pipe and put	well is 3755's mented on to ut well and f 5' to 3285'. at top of Sal up regulation	p of anhydrite found junk at 3 Will set brid lt. Will set 1 on marker.  R  By  Position 0	at 3425' is ce at 1741' with 385'. Will se a 30 foot coment.  Dechicchis  Company or Operat	emented with 100 sacks to 100 footement plug in
cotal depth of this 125 sacks. 10" is continued to clean on the complete of the continue from 338; brown 1790' to 1760' fourface pipe and put	well is 3755's mented on to ut well and for to 3285'. at top of Sal up regulation 11 1952	p of anhydrite found junk at 3 Will set brid lt. Will set 1 on marker.  R  By  Position O Send	at 3425' is contact at 1741' with 1385'. Will so as 30 foot coment.  Dechicohis  Company or Operat	emented with 100 sack of 100 footement plug in