

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

July 6, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company State **"N"** Well No. **6** in **"J"**
(Company or Operator) (Unit)
Lot 10 1/4 of Sec. **1**, T. **21-S**, R. **35-E**, NMPM, **Sumont** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to squeeze existing perforations and re-perforate in the Seven Rivers Pay Zone as following:

- (1) Kill well with oil and pull tubing
- (2) Run tubing with retrievable cement retainer and set at approximately 3665' and squeeze cement perforations 3700' - 3745'.
- (3) When squeeze is obtained, reverse out excess cement and pull tubing. Run 4 3/4" bit and easing scraper and drill cement and test squeeze. Drill cast iron bridging plug and clean out to bottom.
- (4) Run tubing with retrievable cement retainer and set at 3790' and squeeze cement perforations 3794' - 3810'.
- (5) Run casing collar survey and perforate 5-1/2" casing from 3764' - 3780' with 4 bullet shots per foot.

Approved....., 19.....
Except as follows:

Shell Oil Company

Company or Operator

Original signed by

By **D. C. Meyers** **D. C. Meyers**

Position **Division Mechanical Engineer**

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By *[Signature]*

Title.....

Name **Shell Oil Company**

Address **Box 1957, Hobbs, New Mexico**