

1cc- Mr. FHR-HFD-f

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

DUPLICATE

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	xx	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)April 25, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Sinclair Oil & Gas Company - State Lea 407 Well No. 4 in 1 (Unit)
 NW 1/4 1/4 of Sec. 2, T. 21S, R. 35E, NMPM, Eumont Pool
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 3925 - PB 3920-

5 1/2" OD Casing @ 3924' - Top cement behind 5 1/2" OD Casing @ 1270' f/ surface-
 Perforated 5 1/2" OD Casing f/ 3806 to 3846' w/ 4 Jet shots per Ft. - Acidized w/ 500 Gal. Mud.
 swabbed dry- verh slight show gas-
 Sand-Oil Fractured w/ 6000 Gal. & 6000# Sand - Swabbing 2 Bbl. load oil per day w/ 1094 MCF Gas.
 Set retainer @ 3750' Squeezed off Perf. f/ 3806-3846' w/ 100 Sk. Drilled cement & Retainer
 to 3920' - Re-perforated w/ 4 Jet shots per Ft. from 3832 to 3846' - Acidized w/ 500 Gal. mud-
 Swabbed dry- no oil or gas- Fractured w/ 3000 Gal. oil & 2400# Sand- Max. Press. 6300#- Swabbed
 1 Bbl. load oil in 12 Hrs. - Perforated Csg. w/ 1-2" Formation Fracturing gun @ 3835' & Acidized
 w/ 500 Gal. mud- & Fractured w/ 4000 Gal. oil & 4000# Sand- Max. Press. 5300#- Perforated w/ 1-2"
 Formation Fracturing gun again @ 3835' no results- Tested 2 Bbl. load oil per day w/ 1462 MCF
 gas per day @ 250#- Non- commercial and pull
 Propose to cover perforations w/ cement plug in bottom- Knock off 5 1/2" OD Casing @ Approx.
 1200' and set 25 Sk. cement plug, set cement plug (25 Sk.) in bottom of Surface Casing @ 314 Ft.
 Set "Regulation Marker" in top of 8 5/8" OD Surface Casing & in bottom of cellar- 4" extending
 4 Ft. above surface lever- fill cellar & pits - Keeping hole full heavy mud.

Approved: April 24, 1956, 19.....
Except as follows:Sinclair Oil & Gas Company
Company or Operator

By: C.C. Salter

Position: Dist. Supt.

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By: W. Armstrong

Name: C.C. Salter

Title:

Address: 520 E. Broadway, Hobbs, N.M.

