

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

(Form C-102)  
(Revised 7/1/52)

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be furnished to the Bureau on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (NARO)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>FRAC</b>	<b>X</b>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Roswell, New Mexico  
(Place)

September 7, 1961  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company State M Well No. 1 in H  
(Company or Operator) Lease (Unit)  
Lot 8 1/4 of Sec. 1, T. 21S, R. 35E, NMPM., Rumont Pool  
(40-acre Subdivision)  
Lea County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

**Proposed Operation:**

1. Pull rods, pump and tubing.
2. Plug back w/sand to 3810', w/Hydromite to 3806' and cap w/Wellex squeeze gun.
3. Run 3 1/2" tubing w/Lynes packer and set at 3740'.
4. Swab test. If water shut off is effective, proceed w/frac.
5. Treat via 3 1/2" tubing w/30,000 gallons lease crude + 1 1/2#/gallon 20-40 mesh sand plus sufficient fluid loss additive to give spurt loss less than 10 cc and 30 minute fluid loss less than 25 cc.
6. Shut in overnight.
7. Bleed off pressure, pull 3 1/2" tubing.
8. Run 2 1/2" tubing, check for fill, clean out if necessary and swab test.
9. Run rods and pump and place on production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

Shell Oil Company

Company or Operator  
By..... R. A. Lowery Original Signed By  
R. A. LOWERY  
Position..... District Exploitation Engineer  
Send Communications regarding well to:

Name..... Shell Oil Company  
Address..... Box 1858, Roswell, New Mexico