

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE OLD PERFORATIONS	X	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO OIL PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico
(Place)

February 5, 1958
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the..... State M

Shell Oil Company
Lot 8 (Company or Operator) Well No. 1 in H
1/4 (40-acre Subdivision) 1/4 of Sec. 1, T. -21-S, R. -35-E, NMPM, Eumont (Unit)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. RUPU, kill well & load hole w/inverted emulsion mud.
2. Pull tubing (including stinger)
3. Run tubing w/bit & drill up Baker Model D production packer.
4. Pull tubing & bit.
5. Fill open hole to 3745' w/pea gravel & cap w/approximately 2 sx. Calseal.
6. Run tubing open ended to 3730' & spot 1600 gallons Cealment thru tubing. When tubing & annulus are equalized w/Cealment, pull tubing up to 2000'.
7. Bradenhead squeeze to 1000 psi. Pull tubing. WOC 72 hours.
8. Drill out to 3075'. Test casing w/1000 psi.
9. If OK, drill to 3340' & retest. If not, recement.
10. If OK, drill to 3680' & retest. If not, recement.
11. Drill & clean out to TD 3847'.
12. Pull tubing & bit.
13. Run 2 1/2" tubing with seating nipple.
14. Swab test & place on production.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Shell Oil Company

Company or Operator
By Rex C. Cabaniss Original Signed By Rex C. Cabaniss

Position..... District Exploitation Engineer
Send communication regarding well to:

Name Shell Oil Company
Box 845
Address Roswell, New Mexico