


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	
X	

December 15, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Cities Service Oil Company

State "B"

Well No. 4

in the

Company or Operator

Lease

C NW 1/4 SE

of Sec. 7

T. 21S

R. 35E

, N. M. P. M.,

West Eunice

Field,

Lea

County.

The dates of this work were as follows: December 12 & 13, 1947

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on December 10, 1947

and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was drilled to a total depth of 3848' in lime with 8 5/8" casing set at 262' and cemented to surface, and 5 1/2" CD casing set at 3633' and cemented with 350 sacks. After drilling to total depth the well was tested by swabbing and produced no oil, 5 barrel water per hour and no gas. The open hole was cemented with 25 sacks. Shot 5 1/2" casing at 692' and pulled same. The hole was loaded with mud, spotted 25 sacks above the place where 5 1/2" casing was shot off and spotted 25 sacks of cement inside surface pipe to the surface with a 4" pipe set in cement for marker. Cementing was done by Halliburton Oil Well Cementing Company.

Witnessed by R. W. Ely Cities Service Oil Company District Superintendent
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

15th day of December, 1947

Name

Position District Superintendent

Representing Cities Service Oil Company
Company or Operator

My commission expires March 12, 1951

Address Drawer G., Hobbs, New Mexico

Remarks:

APPROVED

DEC 18 1947

OIL & GAS INSPECTOR

Title