NUMBER . CU .				1
011	TRIBUTI	N		L
SANTA FE				1
FILE			t	t.
U.S.G.S.				ľ
LAND OFFICE			ł	f
TRANSPORTER	OIL		t	1
	GAS			
PROBATION OFFIC	έκ.			
OPERATOR				

## EW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which while given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	NOTICE OF INTENTION TO PLUG BACK		Notice of Intention to Set Liner	
Notice of Intention to Squeeze	NOTICE OF INTENTION TO ACEDIZE		Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	NOTICE OF INTENTION (OTHER) Plug back	x	NOTICE OF INTENTION (OTHER)	
OIL CONSERVATION COMMISSIO SANTA FE, NEW MEXICO Gentlemen:	and complete as wat ON <u>Artesis</u> New (Place)			24, 1964
	to do certain work as described below a	t the	Wilson Oil Compan	<b>X</b>
	Shell St	ate	Well No	C
(Company or O) NE 1/ NW 1/4 of Sec (40-acre Subdivision)	7 , T. 215 , 355		Wilson	(Unit) Poo
Les	County.		,	
	FULL DETAILS OF PROPOSED			

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The subject well was drilled to 3862'. Deepened to 3955' with top original pay 3845-62'. The well is temporarily abandoned. Permission is requested to abandon the producing zone by setting cast iron bridge plug in 7" casing (set at 3648', cemented 200 sx). The casing, at this time, will not be pulled, but will be perforated at 900-50 and 1200-50' in an effort to obtain fresh water for drilling purposes. The final plugging will be submitted for your approval at the abandonment of the water zones. Wells drilled under identical circumstances and having 7" casing cemented with 200 sx, have found the top of cement at about 1500', which would be 100' above the top of anhydrite.

Approved, 19, 19	Wilson Oil Company				
Except as follows:	Company or Operator				
	Ву				
	Position				
OIL CONSERVATION COMMISSION	Send Communications regarding well to:				
By A Ang	Name				
Title	Address Box 457, Artesia, New Mexice				