


DUPLICATE

FORM C-105

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

M. D. Bryant-Drilling & Exploration Co., Inc., Box 1575, Hobbs, New Mexico
Company or Operator Address
State **35E** Well No. **2** in **SW-SE** of Sec. **12**, T. **21S**
R. **35E** N. M. P. M. **Eunice** Field, **Lea** County.
Well is **4950** feet south of the North line and **1650** feet west of the East line of **Section 12**
If State land the oil and gas lease is No. **B-1581** Assignment No. **1**
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced **February 5** 19 **39** Drilling was completed **March 1** 19 **39**
Name of drilling contractor **Drilling & Exploration Co., Inc.** Address **408 Centinental Bldg., Dallas, Texas**
Elevation above sea level at top of casing **3597** feet.
The information given is to be kept confidential until **Not confidential** 19

OIL SANDS OR ZONES

No. 1, from **3825** to **3908** No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8	28#	8	N.T.Co.	1585	Baker	-	-	-	-
5 1/2	17#	10	Youngtown	3741	"	-	-	-	-

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8 5/8	2011	600	Halliburton	Sp. Gr. 1.20	6 Tons
6 3/4	5 1/2	- 144	75	"	Water	-

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Dowell "X"	1,000	March 3		
		" "X"	2,000	"		
		" "XX"	2,000	"		

Results of shooting or chemical treatment **Estimated natural production was 100 barrels per 24 hours which was increased as below after treating.**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **3908** feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing **March 4** 19 **39**
The production of the first 24 hours was **227** barrels of fluid of which **100** % was oil; - % emulsion; - % water; and - % sediment. Gravity, Be. **35.5**
If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas -
Rock pressure, lbs. per sq. in. -

EMPLOYEES

T. W. Russell Driller **M. N. Crisman** Driller
J. M. McDaniel Driller **M. G. Bruce** Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **13th** **Hobbs, New Mexico** **March 13, 1939**
day of **March** 19 **39** Name **Indigene**
Doris J. Stouff Notary Public Position **Office Manager**
My Commission expires **Aug. 11, 1941** Representing **Drilling & Exploration Co., Inc.**
Address **P.O. Box 1575, Hobbs, New Mexico**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	230	230	Sand
230	846	616	Red bed and Shells
846	1570	724	Red rock
1570	1680	110	Anhydrite
1680	1720	40	Salt
1720	1900	180	Salt and streaks anhydrite
1900	2026	126	Salt and anhydrite shells
2026	2168	142	Salt, Red rock and anhydrite
2168	2205	37	Salt and anhydrite
2205	2641	436	Salt
2641	2882	241	Salt and anhydrite
2882	2965	83	Salt
2965	3100	135	Salt and anhydrite shells
3100	3216	116	Anhydrite
3216	3245	29	Anhydrite and lime
3245	3338	93	Anhydrite
3338	3380	42	Anhydrite and lime
3380	3415	35	Anhydrite
3415	3435	20	Anhydrite and lime
3435	3444	9	Gray lime
3444	3464	20	Anhydrite and lime
3464	3908	444	Lime
			Total depth 3908'