

COPY

DC-122  
Am June 4

DRILLING AND EXPLORATION COMPANY, INC.

P.O. BOX 2075

MAIN OFFICE 030

HOBBS, NEW MEXICO

May 21, 1954

1954 MAY 24 AM 9:41

Schlumberger log file

Oil Conservation Commission  
Box 871  
Santa Fe, New Mexico

Gentlemen:

Application is hereby submitted to drill complete Drilling & Exploration Company, Inc., State Indura Well No. 4, located 1900 feet from South line and 660 feet from East line of Section 12, Township 21 South, Range 35 East, Lea County, New Mexico.

Notice of Intention to Drill, Form C-101, was filed on March 5, 1954 and approved March 8, 1954. Total depth of 3911 feet was reached on May 6, 1954 and 5-1/2-inch casing was cemented at 3910 feet with 800 sacks cement. Temperature Survey indicates top of cement behind casing to be at 1250 feet. The cement plug was drilled out to 3909 feet.

The 5-1/2-inch casing was perforated opposite the Queen formation from 3855 to 3908 feet and from 3790 to 3834 feet with four jet shots per foot. The interval from 3855 to 3908 was treated with 6,000 gallons crude carrying one pound sand per gallon with packer set at 3825 feet. The interval 3790 to 3834 was treated with 6,000 gallons crude with one pound sand per gallon with bridging plug set at 3845 feet and packer set at 3700 feet. On potential test flowed 98.15 barrels oil, no water, in 6 hours for a 24-hour potential of 392.60 barrels oil with gas-oil ratio of 750 cubic feet gas per barrel.

It is proposed to perforate the 5-1/2-inch casing opposite the Seven Rivers formation of the Jalco Gas Pool from 3350 to 3410, 3520 to 3540, 3590 to 3570, 3610 to 3650 and from 3730 to 3750 feet. Two-inch tubing will be run to approximately 3800 feet with a Street Model ND hookball packer set at approximately 3775 feet. In this manner it is proposed to produce oil from the Queen formation of the Eunice-Mountant Oil Pool through 2-inch tubing and gas from the Seven Rivers formation of the Jalco Gas Pool through casing-tubing annulus.

COPY

DRILLING AND EXPLORATION COMPANY, INC.

MAIN OFFICE 010

P.O. BOX 2075

HOBBS, NEW MEXICO

MAY 21 1954

MAY 21, 1954

Oil Conservation Commission  
Box 871  
Santa Fe, New Mexico

Gentlemen:

Application is hereby submitted to drill complete drilling & Exploration Company, Inc., State Brubaker Well No. 4, located 1250 feet from South line and 600 feet from East line of Section 12, Township 21 South, Range 32 East, Lea County, New Mexico.

Notice of intention to drill, Form O-101, was filed on March 2, 1954 and approved March 8, 1954. Total depth of 3911 feet was reached on May 6, 1954 and 2-1/2-inch casing was cemented at 3910 feet with 800 sacks cement. Temperature survey indicated top of cement behind casing to be at 1250 feet. The cement plug was drilled out to 3909 feet.

The 2-1/2-inch casing was perforated opposite the Green formation from 3855 to 3908 feet and from 3790 to 3834 feet with four feet apart per foot. The interval from 3855 to 3908 was treated with 6,000 gallons grade carrying one pound sand per gallon with packer set at 3855 feet. The interval 3790 to 3834 was treated with 6,000 gallons grade with one pound sand per gallon with bridging plug set at 3855 feet and packer set at 3700 feet. On potential test flowed 22.12 barrels oil, no water, in 6 hours for a 24-hour potential of 22.60 barrels oil with gas-oil ratio of 780 cubic feet gas per barrel.

It is proposed to perforate the 2-1/2-inch casing opposite the Seven Rivers formation of the same gas pool from 3350 to 3410, 3520 to 3540, 3550 to 3570, 3610 to 3650 and from 3730 to 3750 feet. Two-inch tubing will be run to approximately 3800 feet with a Sweet Metal HD hookwell packer set at approximately 3775 feet. In this manner it is proposed to produce oil from the Green formation of the Seven Rivers Oil Pool through 2-inch tubing and gas from the Seven Rivers formation of the same Gas Pool through casing-tubing annulus.