NEW XICO OIL CO	INSERVATION COM [*] 3SION	
Santa Santa	Fe, New Mexico	
	NEOUS NOTICES	9.240
Submit this notice in tripidate to the Oil Conservation been. A sopy will be returned to the sender on which advisable, or the rejection by the Commission or its followed, and work should not begin until approval is o of the Commission.	Commission or its proper agent herore illegroup th will be given the approval, with the plan submitted. The plan submitted. The plan submitted is the plan	social is to the considered of the aid be aid Regulation
	notice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WEL	
NOTICE OF ANTENTION TO DEEPEN WELL	;	
Hebbs,	Vew Mexico April 16, 1	940
OIL CONSERVATION COMMISSION,		
Santa Fe, New Mexico. Gentlemen:		
Following is a notice of intention to do certain work a	described below at the	
Shell Oil Company Inc. Stat		
f Sec. 12 , T. 21S , R. 35E	_, N. M. P. M.,Eunice	Field
County.		
FOLLOW INSTRUCTIONS IN THE RUL	ROPOSED PLAN OF WORK ES AND REGULATIONS OF THE COMMISSION	
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte	nded
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off w and after drilling the cement plug, wor	ES AND REGULATIONS OF THE COMMISSION 76° and cemented to the surface wi D A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8* casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off w and after drilling the cement plug, wor	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi 0 A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor rk to begin at 5:00 P.M. April 15,	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off was and after drilling the cement plug, wor APR 18 1940 pproved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi 0 A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor rk to begin at 5:00 P.M. April 15,	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off was and after drilling the cement plug, wor APR 18 1940 pproved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi O A.M. April 14, 1940. It is inte with 1000 lb. for 30 minutes befor 9k to begin at 5:00 P.M. April 15, Shell 011 Company, Inc.	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off was and after drilling the cement plug, wor APR 18 1940 pproved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi 0 A.M. April 14, 1940. It is inter with 1000 lb. for 30 minutes befor rk to begin at 5:00 P.M. April 15, Shell 0il Company, Inc.	ndød e
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off was and after drilling the cement plug, wor APR 18 1940 pproved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi 0 A.M. April 14, 1940. It is inter with 1000 lb. for 30 minutes befor rk to begin at 5:00 P.M. April 15, 	nded e 194 9 .
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r and after drilling the cement plug, wor APR 18 1940 pproved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi D A.M. April 14, 1940. It is intended with 1000 lb. for 30 minutes befor rk to begin at 5:00 P.M. April 15, rk to begin at 5:00 P.M. April 15, Shell Oil Company, Inc. District Engineer	nded e 1940.
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off was and after drilling the cement plug, wor APR 18 1940 pproved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi D A.M. April 14, 1940. It is intended with 1000 lb. for 30 minutes befor rk to begin at 5:00 P.M. April 15, rk to begin at 5:00 P.M. April 15, Shell Oil Company, Inc. Company of Operator By Position District Engineer Send communications regarding w NameT.B. Lambert	nded e 1940.
FOLLOW INSTRUCTIONS IN THE RUL 7 5/8" casing was run to 15 650 sacks of cement. Plug Down at 5:00 to test the casing and water shut off r and after drilling the cement plug, wor APR 18 1940 Approved	ES AND REGULATIONS OF THE COMMISSION 76' and cemented to the surface wi D A.M. April 14, 1940. It is inter with 1000 lb. for 30 minutes befor rek to begin at 5:00 F.M. April 15, Company of Operator By Position_District Engineer Send communications regarding w NameT.B. Lambert	nded e 1940.

Form C-102