

**DUPLICATE**

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS REPORTS ON WELL**

**RECEIVED**  
**MAR 31 1942**  
**HOBBBS OFFICE**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>X</b>		

**Hobbs, New Mexico, March 25, 1942**

Place

Date

OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

**DRILLING & EXPLORATION CO., INC.**, et al., **STATE "H"** Well No. **1** in the  
Company or Operator Lease

**SW/4** of Sec. **17**, T. **21S**, R. **35E**, N. M. P. M.,  
**Eunice** Field, **Lea** County

The dates of this work were as follows: **March 21, 1942**

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on **March 19,** 19 **42**  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

This well was plugged by allowing a 4 sack Calseal bridge at 3400' to set for 45 minutes and a 10 sack cement plug placed on top of this bridge. Another 4 sack Calseal bridge was set at 1780' on top of which 10 sacks of cement were placed. The top of the 8-5/8" casing - 234' left in hole - was plugged with 10 sacks of cement and the location marked by a steel pipe 4" in diameter and 4' left protruding above the 8-5/8" casing. Heavy drilling mud filled that part of the hole not occupied by plugs.

Witnessed by Glenn Staeh Gulf Oil Corp. Field Foreman  
Name Company Title

Subscribed and sworn to before me this

**25th** day of **March**, 19 **42**

[Signature]  
Notary Public

My Commission expires **December 11, 1943**

I hereby swear or affirm that the information given above is true and correct.

Name D. A. Powell

Position D. A. Powell, Vice-President

Representing DRILLING & EXPLORATION CO., INC.  
Company or Operator

Address Box 1575, Hobbs, New Mexico

Remarks:

Roy Yarrhrough  
Name  
**OIL & GAS INSPECTOR**  
Title

718

121.121

121.121