


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

DRILLING & EXPLORATION CO., INC. et al **Box 1575, Hobbs, New Mexico**
 Company or Operator Address
STATE "H" Well No. **1** in **SW/4** of Sec. **13**, T. **21-S**
 Lease
 R. **35-E**, N. M. P. M., **Eunice** Field, **Lea** County.
 Well is **4290** feet south of the North line and **4480** feet west of the East line of **Section 13**
 If State land the oil and gas lease is No. **B-1399** Assignment No. _____
 If patented land the owner is _____, Address _____
 If Government land the permittee is _____, Address _____
 The Lessee is _____, Address _____
 Drilling commenced **February 25,** 19 **42** Drilling was completed **March 18,** 19 **42**
 Name of drilling contractor **DRILLING & EXPLORATION CO., INC.**, Address **Box 1575, Hobbs, New Mexico**
 Elevation above sea level at top of casing **3577** feet.
 The information given is to be kept confidential until **not confidential** 19 ____.

OIL SANDS OR ZONES

No. 1, from **none** to _____ No. 4, from _____ to _____
 No. 2, from _____ to _____ No. 5, from _____ to _____
 No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **230** to **240** feet. **Quantity not determined**
 No. 2, from _____ to _____ feet. _____
 No. 3, from _____ to _____ feet. _____
 No. 4, from _____ to _____ feet. _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8-5/8	24	8	JAL	284	Larkin	-	-	-	Water string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	297	100	Halliburton	Sp. Gr. 1.20	10 tons

PLUGS AND ADAPTERS

Heaving plug—Material **none** Length _____ Depth Set _____
 Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		none				

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **4006** feet, and from _____ feet to _____ feet
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing **-** 19 ____
 The production of the first 24 hours was **-** barrels of fluid of which **-** % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
 If gas well, cu. ft. per 24 hours **-** Gallons gasoline per 1,000 cu. ft. of gas **-**
 Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Posey Henderson, Driller **R. M. Barrington**, Driller
H. D. Pyke, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **19th**day of **March**, 19 **42**

Notary Public

My Commission expires **December 11, 1943**

Hobbs, New Mexico, March 19, 1942
 Place Date

Name **D. A. Powell**Position **D. A. Powell, Vice-President**Representing **DRILLING & EXPLORATION CO., INC.**
Company or OperatorAddress **Box 1575, Hobbs, New Mexico**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	180	180	Caliche Sand
180	230	50	Red Bed
230	240	10	Sand - carrying water
240	449	209	Red Bed
449	1680	1231	Red Rock
1680	1800	120	Red Rock and Anhydrite
1800	3360	1560	Salt and Anhydrite
3360	3670	310	Anhydrite and Lime
3670	4006	336	Lime with streaks of sand
		4006	TOTAL DEPTH