

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1955 AUG 12 PM 3:17

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS	<input checked="" type="checkbox"/>	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

August 12, 1955

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Morris R. Antweil, Oil

(Company or Operator)

Malco State

(Lease)

Jennings Drilling Company

(Contractor)

Well No. 1 in the NE 1/4 SW 1/4 of Sec. 14,

T. 21, R. 35, NMPM., Undesignated Pool, Lea County.

The Dates of this work were as follows: July 2, 1955 July 26, 1955

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Drilled 323'. Set and cemented 323' of 8 5/8" Casing at 323', with 150 sacks cement. Cement circulated to surface. WOC 24 hours. Drilled out and tested for water shut-off 630# for 30 minutes with no decline in pressure observed. Drilled to 3929', 5 1/2", 15 1/2". Set at 3929' with 220 sacks cement. Perforated from 3891-97 with 6 shots per ft. Fraced with 8000 oil and 8000 # sand. Swabbed dry. Squeezed perforations with 75 sacks cement. Perf. 3913' - 3918' with 6 shots per ft. Fraced with 3000 gals oil and 3000 # sand. Swabbed 90% water. Prep to P&A.

Witnessed by B. J. Taber Jennings Drilling Company Drilling Supt.
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name A. J. Davis, Jr.

Position Geologist

Representing Morris R. Antweil, Oil Operat

Address P. O. Box 1058, Hobbs, New M

(Title)

(Date)