

A 10x10 grid with a dot in the top right corner. The dot is located in the first row, eighth column from the left.

**NEW MEXICO OIL CONSERVATION COMMISSION**

**Santa Fe, New Mexico**

## WELL RECORD

**Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies**

AREA 640 ACRES  
LOCATE WELL CORRECTLY

**REGISTER & SUBSCRIPTION**

.....  
(Company or Operator)

## Phillips State

(1999)

Well No. C-1, in NE ¼ of NE ¼, of Sec. 32, T. 21 South, R. 35 East, NMPM.

## San Simon

**Pool ..... Jan**

...County.

Well is 330 feet from North line and 990 feet from East line.

of Section 32 If State Land the Oil and Gas Lease No. is B-1984

Drilling Commenced.....**February 8**....., 19**58**.... Drilling was Completed.....**February 16**....., 19**58**

Name of Drilling Contractor..... **Carper Drilling Company** .....

Address.....**Artesia, New Mexico**.....

Elevation above sea level at Top of Tubing Head.....**3644**..... The information given is to be kept confidential until  
..... 19.....

### OIL SANDS OR ZONES

No. 1, from 3815 to 3832 No. 4, from \_\_\_\_\_ to \_\_\_\_\_

No. 2, from 3790 to 3800 No. 5, from.....to.....

No. 3, from 3778 to 3786 No. 6, from ..... to .....

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from ..... to ..... feet. ....

No. 2, from ..... to ..... feet.

No. 3, from ..... to ..... feet.

No. 4, from.....to.....feet. ....

## CASING RECORD

ORDERING RECORD							
SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	NEW	271				
5 1/2	14	"	3847				

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	8 5/8	271	200	Halliburton		
7 7/8	5 1/2	3847	400	"		

## RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perf. 3815-32. Water fractured w/20,000 lbs. sd. and 15,000 gals. water. Set bridge plug @ 3808'. Perf 3776-86 and 3790-3800 and fractured w/20,000 lbs. sd. in 15,000 gals. water.

**Result of Production Stimulation.....**

...Depth Cleaned Out.....~~3847~~.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3847 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing February 18, 1958

OIL WELL: The production during the first 24 hours was 60 barrels of liquid of which 100 % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 36

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1800	T. Devonian	T. Ojo Alamo	
T. Salt 1940	T. Silurian	T. Kirtland-Fruitland	
B. Salt 3465	T. Montoya	T. Farmington	
T. Yates	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers	T. McKee	T. Menefee	
T. Queen	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	275		Red sand, caliche				
275	1747		Red bed				
1747	1940		Red bed and anhy				
1940	2929		Salt				
2929	3465		Salt and anhy				
3465	3640		Anhy				
3640	3715		Lime				
3715	3848		Sand and Dole				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

February 24, 1958 (Date)  
Company or Operator Resler & Sheldon Address 302 Carter Bldg., Artesia, New Mexico  
Name Velasquez Position or Title