



AREA 640 ACRES  
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

DECLARED BY Phillips State "C"  
(Company or Operator) (Date)  
Well No. 2, in SE  $\frac{1}{4}$  of SE  $\frac{1}{4}$ , of Sec. #8, T. 21 South, R. 35 East, NMPM.  
San Simon Pool, Lea County.  
Well is 1650 feet from North line and 660 feet from East line  
of Section 32. If State Land the Oil and Gas Lease No. is 8-1924  
Drilling Commenced May 15, 1958. Drilling was Completed May 23, 1958.  
Name of Drilling Contractor Carper Drilling Company  
Address Artesia, New Mexico  
Elevation above sea level at Top of Tubing Head..... The information given is to be kept confidential until  
....., 19.....

OIL SANDS OR ZONES

No. 1, from 3820 to 3928 No. 4, from..... to.....  
No. 2, from..... to..... No. 5, from..... to.....  
No. 3, from..... to..... No. 6, from..... to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from..... to..... feet.  
No. 2, from..... to..... feet.  
No. 3, from..... to..... feet.  
No. 4, from..... to..... feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
<u>8 5/8</u>	<u>24</u>	<u>New</u>	<u>265</u>				
<u>5 1/2</u>	<u>14</u>	<u>"</u>	<u>39 1/2</u>				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
<u>11</u>	<u>8 5/8</u>	<u>265m</u>	<u>200</u>	<u>Halliburton</u>		
<u>7 7/8</u>	<u>5 1/2</u>	<u>39 1/2</u>	<u>400</u>	<u>"</u>		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Fractured 20,000 lbs. of water 3910-28  
" " " " " 3870-96  
" " " " " 3820-54

Result of Production Stimulation Increased yield to 55 BOPD  
Depth Cleaned Out 3942

FOOD OF DRILL-STEM AND SPECIAL TV

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3942 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing May 26, 19 58

OIL WELL: The production during the first 24 hours was 55 barrels of liquid of which 100 % was  
was oil; % was emulsion; % water; and % was sediment. A.P.I.  
Gravity 38

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of  
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt 3580	T. Montoya	T. Farmington
T. Yates 3762	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash.	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1800		Red beds & sand				
1800	1940		Anhy				
1940	3580		Salt & anhy				
3580	3800		Anhy				
3800	3942		Sand with lime stringers				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 26, 1958 (Date)  
Company or Operator RESLER & SHELDON Address 302 Carper Bldg., Artesia, New Mexico  
Name Mary Kantor Position or Title Secretary