

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL			
NOTICE OF INTENTION TO DEEPEN WELL		NOTICE OF INTENTION TO PLUG WELL	<b>XX</b>

HOBBES, NEW MEXICO

Place

APRIL 30, 1944

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_

**SKELLY OIL COMPANY** STATE **N.M.** Well No. **1** in **CSE SE**  
Company or Operator Lease  
of Sec. **32**, T. **21 S**, R. **35 E**, N. M. P. M., **San Simon** Field,  
**Lee** County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Drilled to total depth 4020' encountering salt water 3987' to 4000' and 4012' to 4020' in sand which tested flush 4 to 5 bbls water per hour and settled to 1 1/2 barrels water per hour on 18 hour bailing test. Since water encountered correlates with oil section encountered in State "U" No. 1 south offset producing oil well, will plug and abandon. Lead well plug will be driven to shut off bottom hole water, cement cap run from top of lead well to 3940'. Mud laden fluid will be run from 3940' to base of salt and 15 sacks cement run for cap. Will fill hole thru salt section with mud-laden fluid and place 15 sacks cement for cap at top of salt. Hole will be filled with mud laden fluid to various water formations encountered and cement plug run at each point. All casing except 16" which was cemented at 86' will be pulled. After filling hole to top with mud laden fluid and allowing to settle, cement plug and cap will be run and marker installed in accordance with rules and regulations of the New Mexico Oil Conservation Commission.

Approved \_\_\_\_\_, 19\_\_\_\_  
except as follows:

**SKELLY OIL COMPANY**  
Company or Operator  
By *J. N. Stumway*  
Position **Superintendent**  
Send communications regarding well to  
Name **SKELLY OIL COMPANY**

OIL CONSERVATION COMMISSION,  
By *Roy Underwood*  
Title \_\_\_\_\_

Address **DRAWER "D" HOBBES, N.M.**

