## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION	NOTICE OF INTENTION TO	NOTICE OF INTENTION	
TO CHANGE PLANS	TEMPORARILY ABANDON WELL	TO DRILL DEEPER	
NOTICE OF INTENTION	Notice of Intention	Notice of Intention	
TO PLUG WELL	TO PLUG BACK	TO SET LINER	
Notice of Intention	NOTICE OF INTENTION	NOTICE OF INTENTION	
TO SQUEEZE	TO ACIDIZE	TO SHOOT (Nitro)	
Notice of Intention to Gun Perforate	NOTICE OF INTENTION	Notice of Intention	
TO GUN PERFORATE	(Other)	(Other)	
OIL CONSERVATION COMMISS	ION	•	
SANTA FE, NEW MEXICO	Odeses, Texas. (Place)		31 <u>, 1950</u>
Gentlemen:			
Following is a Notice of Intentio	on to do certain work as described below at the	Stats of New Mexico	
Lario 011 & Cos Compe	operator) Lonse		in
			(Unit)
(40-acre Subdivision)	.35, T	MPM., <b>Uniesignated</b>	Pool
Los	County.		
plug 3600 to 3532 feet	Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co	fect with 20 sacks cem ment plug 2065 to 1998	feet with 20
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1 ground. Fill in cellar	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ng 350 to 254 feet with 30 sac 0 sacks cement. Fut piece of 4 and clean location.	feet with 20 sacks cem ment plug 2065 to 1998 iks cement. Spot cement pipe in surface cement	feet with 20 plug in suffa at extending 4
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Gar	fect with 20 sacks cem ment plug 2055 to 1998 aks cement. Spot cement " pipe in surface ceme per Drilling Company, I	feet with 20 plug in suffa at extending 4
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Car Arte	feet with 20 sacks cem ment plug 2065 to 1998 iks cement. Spot cement pipe in surface cement	feet with 20 plug in suffa at extending 4
Total depth drilled - Fill casing with mmd. plug 3600 to 3532 feet cement. Spot cement pl sero to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Gar Arte	fect with 20 sacks cem ment plug 2055 to 1998 aks cement. Spot cement " pipe in surface ceme per Brilling Company, I per Building	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sero to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co- ing 350 to 254 feet with 30 sac 0 sacks cement. Fut piece of A and clean location. woration Car Arte Arte	feet with 20 sacks cem ment plug 2065 to 1998 aks cement. Spot cement " pipe in surface ceme per Brilling Company, I per Building ssia, New Metico entions Mr. Tracey Clar	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mmd. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Gil & Refining P.O. Bex 1287	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co- ing 350 to 254 feet with 30 sac 0 sacks cement. Fut piece of A and clean location. woration Car Arte Arte	feet with 20 sacks cem ment plug 2055 to 1998 sks cement. Spot cement " pipe in surface ceme per Brilling Company, I ber Building ssia, New Metice entions Mr. Tracey Clar Coll Corporation	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mmd. plug 3600 to 3532 feet cement. Spot cement pl scro to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Gil & Refining P.O. Box 1287 Reswell. New Mexice	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Fut piece of A and clean location. woration Car Arto Arto Company Guin Box Reso	feet with 20 sacks cem ment plug 2055 to 1998 sks cement. Spot cement " pipe in surface ceme per Brilling Company, I ber Building ssia, New Metice entions Mr. Tracey Clar Coll Corporation	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mmd. plug 3600 to 3532 feet cement. Spot cement pl scro to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Gil & Refining P.O. Box 1287 Reswell. New Mexice	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Gar Arte Arte Company Guin Box Results	feet with 20 sacks cem ment plug 2065 to 1998 sks cement. Spot cement " pipe in surface ceme er Drilling Company, I ber Building ssia, New Metico entions Mr. Tracey Clar Coll Corporation 669 well, New Mexice	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sero to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Qil & Refining P.O. Bex 1287 Reswell, New Mexice Attentions Mr. James A	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Gar Arte Arte Company Guin Box Results	feet with 20 sacks cem ment plug 2065 to 1998 sks cement. Spot cement " pipe in surface ceme per Brilling Company, I per Building ssia, New Metico entions Mr. Tracey Clar Coll Corporation 669	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Qil & Refining P.O. Bex 1287 Reswell, New Mexice Attentions Mr. James A	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Gar Arte Arte Company Guin Box Results	feet with 20 sacks cem ment plug 2055 to 1998 sks cement. Spot cement " pipe in surface ceme er Drilling Company, I ber Building saia, New Metico entions Mr. Tracey Clar Cil Corporation 669 well, New Mexice	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mad. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Qil & Refining P.O. Bex 1287 Reswell, New Mexice Attentions Mr. James A	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co ing 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Gar Arte Arte arnwall Atte Company Guin Box Rest . Davidson 19	feet with 20 sacks cem ment plug 2065 to 1998 sks cement. Spot cement " pipe in surface ceme per Brilling Company, I ber Building beia, New Metico entions Mr. Tracey Clar Coll Corporation 669 well, New Mexice to Oil & Gas Com any geompany or Operator	feet with 20 plug in suffa at extending 4 nc.
Total depth drilled - Fill casing with mnd. plug 3600 to 3532 feet cement. Spot cement pl sero to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Gil & Refining P.O. Bex 1287 Resvell, New Mexice Attentions Mr. James A Approved	4050 feet. Spot cement plug 4050 to 3978 i with 20 sacks cement. Spot coming 350 to 254 feet with 30 sacks o sacks cement. Fut piece of A i and clean location. woration Car Arta Arta Arta Company Guin Box Resu . Davidson 19	feet with 20 sacks cem ment plug 2055 to 1998 sks cement. Spot cement " pipe in surface ceme er Drilling Company, I ber Building saia, New Metico entions Mr. Tracey Clar Cil Corporation 669 well, New Mexice	feet with 20 plug in suffa at extending 4 nc. k
Total depth drilled - Fill casing with mmd. plug 3600 to 3532 feet cement. Spot cement pl soro to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Gil & Refining P.O. Box 1287	4050 feet. Spot cement plug 4050 to 3978 i with 20 sacks cement. Spot coming 350 to 254 feet with 30 sacks o sacks cement. Fut piece of A i and clean location. woration Car Arta Arta Arta Company Guin Box Resu . Davidson 19	feet with 20 sacks cem ment plug 2055 to 1998 aks cement. Spot cement " pipe in surface ceme per Brilling Company, I per Building osia, New Metico entions Mr. Tracey Clar Coll Carporation 669 well, New Mexico i. Oil & Gas Com any Sompany or Operator Sompany or Operator Contemporation Sompany or Operator	feet with 20 plug in suffa at extending 4 nc. k
Total depth drilled - Fill casing with mmd. plug 3600 to 3532 feet cement. Spot cement pl sere to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Gil & Refining P.O. Bex 1287 Resvell, New Mexice Attentions Mr. James A Approved	4050 feet. Spot cement plug 4050 to 3978 with 20 sacks cement. Spot co mg 350 to 254 feet with 30 sac 0 sacks cement. Put piece of A and clean location. woration Carry Arte Arte Company Gulf Box Resu . Davidson 19	feet with 20 sacks cem ment plug 2055 to 1998 aks cement. Spot cement " pipe in surface ceme per Brilling Company, I per Building osia, New Metico entions Mr. Tracey Clar Coll Carporation 669 well, New Mexico i. Oil & Gas Com any Sompany or Operator Sompany or Operator Contemporation Sompany or Operator	feet with 20 plug in suffa at extending 4 nc. k
Total depth drilled - Fill casing with mnd. plug 3600 to 3532 feet cement. Spot cement pl sero to 20 feet with 1 ground. Fill in cellar Amerada Petroleum Corp P.O. Bex 591 Midland, Texas Attentions Mr. John Ce Humble Oil & Refining P.O. Bex 1287 Resvell, New Mexice Attentions Mr. James A Approved	4050 feet. Spot cement plug 4050 to 3978 i with 20 sacks cement. Spot co mg 350 to 254 feet with 30 sac 0 sacks cement. Put plece of A and clean location. Foration Gary Arte Arte Company Guin Box Rest . Davidson 19	foot with 20 sacks com ment plug 2055 to 1998 sks cement. Spot cement " pipe in surface ceme ser Brilling Company, I ber Building saa, New Metico entions Mr. Tracey Clar Conformation (69) well, New Mexico Company or Operator Sompany or Operator Company or Operator	feet with 20 plug in suffa at extending 4 nc. k